



122 RUBBER TAPE

Splicing Compound

Technical Data Sheet **October 2017**

Description and Features **122 Rubber Tape** is a 0,76 mm (30 mil) self-amalgamating, low voltage rubber tape which is **UL-510 Listed** for use as primary insulation at not more than 600 volts. It easily conforms to irregular shapes and surfaces yielding a void free electrically stable build-up. 122 Rubber tape is compatible with all extruded dielectric cable insulations. Meet ASTM D-4388 type I standard.

- Self- amalgamating
- Good electrical properties
- Good conformability

Materials	Backing Rubber	Adhesive none	Color Black	Standard Size Width x Length 19 mm x 6,7 m (0.75 in. x 22 ft.) Other sizes available upon request
------------------	--------------------------	-------------------------	-----------------------	---

Technical Properties	Characteristic	Typical Value	Test Method
	Thickness (mm)	0,76	UL-510
	Tensile strength (MPa)	3,0	UL-510
	Elongation (%)	500	UL-510
	Flammability	Pass	UL-510
	Continuous Operating temp (°C)	80	UL-510
	Weather Resistance	Pass	UL-510
	Dielectric strength (kV/mm)	20	UL-510

Recommended Uses For insulating of splices on solid dielectric cable thru 600 volts in conjunction with a jacketing tape.

Storage In original packaging, placed in horizontal position under cover and temperature between 5°C and 35 °C.

Shelf Life 24 months from date of manufacture.

Information provided is for reference only. Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use

LIMITED WARRANTY: Plymouth warrants that its Product will substantially conform to that products written specifications for a period of one (1) year from the date of shipment, (Unless provided otherwise). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first complied with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (Rev. 1/2017-2019)