



12	Contact Pin	Note 1	Note 3	1
11	Nut	Note 1	Note 2	1
10	Washer	Note 1	Note 2	1
9	Gasket	Silicone	Dark Red	1
8	Braid Clamp	Note 1	Note 2	1
7	Washer	Note 1	Note 2	1
6	Insulator	Note 4	Natural	1
5	Retainer Ring	SUS 304	Note 5	1
4	Gasket	Silicone	Dark Red	1
3	Contact Body	Note 1	Note 2	1
2	Body	Note 1	Note 2	1
1	Shell	Note 1	Note 2	1

NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Albaloy Plating (Copper-Tin-Zinc) Pl. 80 Min, Thick
 3. Gold Pl. 5 Min Thick over Copper Pl. 50 Min. Thick
 4. Teflon
 5. Passivated

RoHS Compliant

Dimensions are in Inches
 Unless Otherwise Specified
 Tolerances
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

Part No.	
Approved	Date 12-14-2018
Checked	Date 12-14-2018
Drawn	Date 12-14-2018

NTE Electronics	
Title N Clamp Plug (For RG-8/U, 213/U, 214/U)	
Drawing No. 06-N004	
File No.	

No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	2.5/1	Issue	A
-----	-------------	----------	--------	------	-------------	-------	-------	-------	---

F
E
D
C
B
A

F
E
D
C
B
A

1 2 3 4 5 6 7 8

1 2 3 4 5 6 7 8