



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>



## NTE639 General Purpose Silicon Rectifier High Voltage, Standard Recovery DO201AD Type Package

**Features:**

- Diffused Junction
- Low Forward Voltage Drop
- High Current Capability
- High Reliability
- High Surge Current Capability

**Maximum Ratings and Electrical Characteristics:**

( $T_A = +25^\circ\text{C}$  unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%)

Maximum Peak Repetitive Reverse Voltage, $V_{RRM}$ .....	1300V
Maximum Working Peak Reverse Voltage, $V_{RWM}$ .....	1300V
Maximum DC Blocking Voltage, $V_R$ .....	1300V
Maximum RMS Reverse Voltage, $V_{R(RMS)}$ .....	910V
Maximum Average Rectified Output Current (.375" (9.5mm) Lead Length, $T_A = +75^\circ\text{C}$ ), $I_O$ .....	3A
Non-Repetitive Peak Forward Surge Current, $I_{FSM}$ (8.3ms Single Half Sine-Wave Superimposed on Rated Load) .....	200A
Maximum Instantaneous Forward Voltage ( $I_F = 3A$ ), $V_{FM}$ .....	1.0V
Maximum Peak Reverse Current ( $V_R = 1300V$ ), $I_{RM}$ $T_A = +25^\circ\text{C}$ .....	5° A
$T_A = +100^\circ\text{C}$ .....	100° A
Typical Junction Capacitance (Note 1), $C_j$ .....	50pF
Operating Junction Temperature Range, $T_J$ .....	-65° to +125°C
Storage Temperature Range, $T_{stg}$ .....	-65° to +150°C
Typical Thermal Resistance, Junction-to-Ambient, $R_{thJA}$ (.375" (9.5mm) Lead Length, $T_A = +25^\circ\text{C}$ ) .....	20°C/W

Note 1. Measured at 1MHz and applied reverse voltage of 4V.

