


Recommended Cable Stripping Dim's

Crimped Ferrule  
Hex Crimp Size .213 (5.41)  
Contact Pin to Solder

RoHS Compliant

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
  2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
  3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
  4. Teflon
  5. Passivated



8	Ferrule	Copper	Note 2	1
7	Cover	Note 1	Note 2	1
6	Gasket	Silicone	Red	1
5	Retainer Ring	SUS 304	Note 5	1
4	Contact Pin	Note 1	Note 3	1
3	Insulator	Note 4	Natural	1
2	Housing with Barrel	Note 1	Note 2	1
1	Shell	Note 1	Note 2	1
No.	Description	Material	Finish	Q'ty

Dimensions are in Inches  
Unless Otherwise Specified  
Tolerances  
0.5-6 = ±0.2  
6-30 = ±0.4  
30-120 = ±0.6  
120-315 = ±1  
315-1000 = ±1.6  
1000-2000 = ±2.4

Part No.	
Approved	Date 5-5-2015
Checked	Date 5-5-2015
Drawn	Date 5-5-2015

<b>NTE Electronics</b>	
Title SMA R/ACrimp Plug (For RG-58, 58A, 58C, 141)	
Drawing No. 06-S009	
File No.	