



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 4. DELRIN

Crimped Ferrule
 Hex Crimp Size .178 (4.5)
 Crimped Contact Pin
 Hex Crimp Size .068 (1.7)

RoHS Compliant

10	Ferrule	Note 1	Note 2	1	
9	Sleeve	Note 4	Natural	1	
8	Contact Pin	Note 1	Note 3	1	
7	Washer	Note 1	Note 2	1	
6	Spring	SK5	Note 2	1	
5	Retaining Ring	Note 1	Note 2	1	
4	Gasket	Rubber	Red	1	
3	Insulator	Note 4	Natural	1	
2	Body	Note 1	Note 2	1	
1	Shell	Note 1	Note 2	1	
No.	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches
 Unless Otherwise Specified
 Tolerances
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

Part No.									
Approved	Date 1-10-2011								
Checked	Date 1-10-2011								
Drawn	Date 1-10-2011								
No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	3/1	Issue	C

NTE Electronics	
Title BNC Crimp Plug (For RG-174, 188, 316, LMR100)	
Drawing No. 06-B015	
File No.	