



Accepts .020 (0.5) to .041 (1.05) Dia. Center Conductor Typical

3/8-32UNEF-2A

1.043 (26.5) Ref.

RoHS Compliant

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Phosphor Bronze
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. TEFLON
 6. BERYLLIUM COPPER

Dimensions are in Inches			
Unless Otherwise Specified Tolerances			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

Part No.	
Approved	Date 2-16-2011
Checked	Date 2-16-2011
Drawn	Date 2-16-2011

NTE Electronics	
Title	BNC Female to F Female Adapter
Drawing No.	06-B027
File No.	

6	Body	Note 1	Note 2	1	
5	Insulator	Note 5	Natural	1	
4	Contact Pin	Note 6	Note 4	1	
3	Contact Pin	Note 3	Note	1	
2	Insulator	Note 5	Natural	1	
1	Housing	Note 1	Note 2	1	
No	Description	Material	Finish	Q'ty	Drawing No.