



Recommended Cable Stripping Dim's

NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Phosphor Bronze
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. Teflon

Crimped Ferrule
 Hex Crimp Size .213 (5.41)
 Crimped Contact Pin
 Hex Crimp Size .068 (1.7)

RoHS Compliant

| | | | | | |
|-----|---------------|----------|---------|------|-------------|
| 10 | Ferrule | Copper | Note 2 | 1 | |
| 9 | Contact Pin | Note 3 | Note 4 | 1 | |
| 8 | Shell | Note 1 | Note 2 | 1 | |
| 7 | Gasket | Rubber | Red | 1 | |
| 6 | Retainer Ring | Note 1 | Note 2 | 1 | |
| 5 | Ring | DELTRIN | Natural | 1 | |
| 4 | Washer | Note 1 | Note 2 | 1 | |
| 3 | Barrel | Note 1 | Note 2 | 1 | |
| 2 | Insulator | Note 5 | Natural | 1 | |
| 1 | Body | Note 1 | Note 2 | 1 | |
| No. | Description | Material | Finish | Q'ty | Drawing No. |

Dimensions are in Inches
 Unless Otherwise Specified
 Tolerances
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

| | |
|----------|------------------|
| Part No. | |
| Approved | Date 6-6-2013 |
| Checked | Date 6-6-2013 |
| Drawn | Date 6-6-2013 |

| | |
|------------------------|--|
| NTE Electronics | |
| Title | TNC Reverse Polarity Crimp Plug (For RG-58C/U, 58U) |
| Drawing No. | 06-T004 |
| File No. | |