



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE3185 Discrete White Clear LED Indicator 3mm (T-1) Type Package

Description:

The NTE3185 is a blue source color LED device made with GaN on SiC in a 3mm (T-1) type package. It is recommended that a wrist strap or anti-electrostatic glove be used when handling this device as static electricity and surge will cause damage. All devices, equipment, and machinery must be electrically grounded.

Features:

- High Efficiency
- White Emission, High Luminous Intensity

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Power Dissipation, P_D	120mW
DC Forward Current, I_F	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width), I_F	100mA
Reverse Voltage, V_R	5V
Operating Temperature Range, T_{opr}	-30° to $+80^\circ\text{C}$
Storage Temperature Range, T_{stg}	-40° to $+100^\circ\text{C}$
Lead Temperature (During Soldering, .157 (4mm) below package base, 5sec max), T_L ...	$+260^\circ\text{C}$

Electro-Optical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	V_F	$I_F = 20\text{mA}$	-	3.6	4.0	V
Reverse Current	I_R	$V_R = 5\text{V}$	-	10	-	μA
Luminous Intensity	I_V	$I_F = 20\text{mA}$	50	-	300	mcd
Viewing Angle	$2\theta^{1/2}$	Note 1	-	40	-	deg.
Chromaticity Coordinates	X		-	0.31	-	
	Y		-	0.32	-	

Note 1. Viewing Angle is the angle from optical centerline where the luminous intensity is half the optical centerline value.

