



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 4. DELRIN

Crimped Ferrule
 Hex Crimp Size .255 (6.5)
 Crimped Contact Pin
 Hex Crimp Size .068 (1.7)

RoHS Compliant

9	Ferrule	Note 1	Note 2	1
8	Contact Pin	Note 1	Note 3	1
7	Washer	Note 1	Note 2	1
6	Spring	SK5	Note 2	1
5	Retaining Ring	Note 1	Note 2	1
4	Gasket	Rubber	Red	1
3	Insulator	Note 4	Natural	1
2	Body	Note 1	Note 2	1
1	Shell	Note 1	Note 2	1

Dimensions are in Inches
 Unless Otherwise Specified
 Tolerances
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

Part No.	
Approved	Date 1-5-2011
Checked	Date 1-5-2011
Drawn	Date 1-5-2011

NTE Electronics	
Title	BNC Crimp Plug (For RG-59, 62)
Drawing No.	06-B013
File No.	

No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	3/1	Issue	A
-----	-------------	----------	--------	------	-------------	-------	-----	-------	---