



NOTES: Finish (Plating Thickness in Micro-inches)

1. Brass
2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
3. Phosphor Bronze
4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
5. TEFLON

Crimped Ferrule
Hex Crimp Size .213 (5.4)
Crimped Contact Pin
Hex Crimp Size .068 (1.7)

RoHS Compliant

No	Description	Material	Finish	Q'ty	Drawing No.
10	Ferrule	Copper	Note 2	1	
9	Contact Pin	Note 2	Note 4	1	
8	Shell	Note 1	Note 2	1	
7	Gasket	Rubber	red	1	
6	Retainer Ring	Note 1	Note 2	1	
5	Spring	SK5	Note 2	1	
4	Washer	Note 1	Note 2	1	
3	Barrel	Note 1	Note 2	1	
2	Insulator	Note 5	Natural	1	
1	Body	Note 1	Note 2	1	

Dimensions are in Inches									
Unless Otherwise Specified Tolerances									
0.5-6	=	±0.2							
6-30	=	±0.4							
30-120	=	±0.6							
120-315	=	±1							
315-1000	=	±1.6							
1000-2000	=	±2.4							
No	Description	Material	Finish	Q'ty	Drawing No.	Scale	3/1	Issue	A

Part No.		<h1 style="text-align: center;">NTE Electronics</h1>
Approved	Date 12-14-2018	
Checked	Date 12-14-2018	
Drawn	Date 12-14-2018	
Title		BNC Reverse Polarity Crimp Plug (For RG-58C/U Cable)
Drawing No.		06-B028
File No.		