



Personal Protective Equipment  Safety Glasses Protective Gloves	WHMIS Pictograms  D2B Toxic	DOT Pictograms <div style="border: 1px solid black; padding: 5px; text-align: center;"> Not Regulated </div>
--	---	---

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Acid LF
MSDS Manufacturer Number: Acid
Product Use/Restriction: Flux cored solder
Manufacturer Name: Kester
Address: 800 W. Thorndale Avenue
 Itasca, IL 60143
General Phone Number: (630)-616-4000
Customer Service Phone Number: (800)-2KESTER (253-7837)
CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300 Outside of the U.S. and Canada: (703) 527-3887
Website: msds@kester.com
MSDS Creation Date: August 15, 2008
MSDS Revision Date: September 30, 2012



HMIS	
Health Hazard	2
Fire Hazard	1
Reactivity	1
Personal Protection	x

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Antimony	7440-36-0	0 - 10 by weight	
Bismuth	7440-69-9	0 - 70 by weight	
Copper	7440-50-8	0 - 10 by weight	
Silver	7440-22-4	0 - 10 by weight	
Tin	7440-31-5	0 - 100 by weight	
Zinc	7440-66-6	0 - 10 by weight	
Zinc Chloride	7646-85-7	0 - 5 by weight	
Aniline Hydrochloride	142-04-1	0 - 5 by weight	

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Severe Irritant. Exposures to soldering fumes and vapors may be irritating to eyes, respiratory system, and skin.
Route of Exposure: Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:
Eye: Smoke during soldering can cause eye irritation.
Skin: May cause skin irritation.
Inhalation: Inhalation of vapors, fumes or mists of the product may be irritating to the respiratory system.
Ingestion: Ingestion of the product may produce gastrointestinal irritation and disturbances.
Target Organs: Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions: None generally recognized.

SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point:	> 93°C (> 199°F)
Lower Flammable/Explosive Limit:	Not applicable.
Upper Flammable/Explosive Limit:	Not applicable.
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Unsuitable Media:	Do not use a solid water stream as it may scatter and spread fire.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Hazardous Combustion Byproducts:	Oxides of carbon, oxides of nitrogen, aliphatic aldehydes, and other organic substances may be formed during combustion.. Zinc oxide

NFPA Ratings:

NFPA Health:	2
NFPA Flammability:	1
NFPA Reactivity:	1

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Avoid breathing vapor, aerosol or mist. Avoid contact with skin, eyes and clothing.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Methods for containment:	Contain spills with an inert absorbent material such as soil, sand or oil dry.
Methods for cleanup:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.

SECTION 7 - HANDLING and STORAGE

Handling:	Corrosive. Use proper personal protective equipment as listed in section 8. Use with adequate ventilation. Avoid breathing vapor and fumes. Use only in accordance with directions.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
Hygiene Practices:	Wash thoroughly after handling. Avoid inhaling vapors, mists, or fumes.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Tightly fitting safety goggles. Wear a face shield also when splash hazard exist.
Hand Protection Description:	Wear appropriate protective gloves. Consult glove manufacturer's data for permeability data. Nitrile rubber or natural rubber gloves are recommended.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other

circumstances where air purifying respirators may not provide adequate protection.

Other Protective:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

PPE Pictograms:



EXPOSURE GUIDELINES

Antimony :

Guideline ACGIH: TLV-TWA: 0.5 mg/m³

Guideline OSHA: PEL-TWA: 0.5 mg/m³

Copper :

Guideline ACGIH: TLV-TWA: 1 mg/m³

Guideline OSHA: PEL-TWA: 1 mg/m³

Silver :

Guideline ACGIH: TLV-TWA: 0.1 mg/m³

Guideline OSHA: PEL-TWA: 0.01 mg/m³

Tin :

Guideline ACGIH: TLV-TWA: 2 mg/m³

Guideline OSHA: PEL-TWA: 2 mg/m³

Zinc Chloride :

Guideline ACGIH: TLV-TWA: 1 mg/m³

TLV-STEL: 2 mg/m³

Guideline OSHA: PEL-TWA: 1 mg/m³

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State:	Solid.
Color:	Silver grey
Odor:	Mild
Melting Point:	> 100°C (> 212°F)
Density:	> 7 g/cm ³ @ 20°C (68°F)
Solubility:	Not miscible or difficult to mix.
Flash Point:	> 93°C (> 199°F)
Explosive Properties:	Product does not present an explosion hazard.

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Heat, flames, incompatible materials, freezing or temperatures below 32 deg. F.
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.

SECTION 11 - TOXICOLOGICAL INFORMATION

Antimony :

Ingestion: Oral - Rat LD50: 100 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Bismuth :

Ingestion: Oral - Mouse LD50: 10 gm/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Rat LD50: 5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Copper :

Ingestion: Oral - Mouse LD50: 413 mg/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Mouse LD50: >5000 mg/kg [Behavioral - Food intake (animal) Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Nausea or vomiting] (RTECS)

Silver :

Ingestion: Oral - Mouse LD50: 100 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Zinc :

Skin: Skin - Human Standard Draize test. : 300 ug/3D-I - [mild](RTECS)

Inhalation: Inhalation - Human TCLo - Lowest published toxic concentration: 124 mg/m³/50M - [Lungs, Thorax, or Respiration - Cough Lungs, Thorax, or Respiration - Dyspnea Skin and Appendages - Sweating] (RTECS)

Ingestion: Oral - Bird duck LDLo: 388 mg/kg - [Autonomic Nervous System - Other (direct) parasympathomimetic oral - Ataxia Blood - changes in leukocyte (WBC) count] (RTECS)

Zinc Chloride :

RTECS Number: ZH1400000

Ingestion: Oral - Rat LD50: 350 mg/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Mouse LD50: 329 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Aniline Hydrochloride :

RTECS Number: CY0875000

Eye: Eye - Rabbit Standard Draize test.: 20 mg/24H (RTECS)

Skin: Administration onto the skin - Rabbit Standard Draize test.: 500 mg/24H (RTECS)

Ingestion: Oral - Rat LD50: 840 mg/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Mouse LD50: 841 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.


SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Not Regulated.

DOT UN Number: Not Regulated.

IATA Shipping Name: Not Regulated.

IATA UN Number: Not Regulated.

DOT Pictograms: 

IMDG UN Number : Not Regulated.

IMDG Shipping Name : Not Regulated.

RID UN Number : Not Regulated.

RID Shipping Name : Not Regulated.

SECTION 15 - REGULATORY INFORMATION

Antimony :

TSCA Inventory Status: Listed

Canada DSL: Listed

Bismuth :

TSCA Inventory Status: Listed

Canada DSL: Listed

Copper :

TSCA Inventory Status: Listed

Canada DSL: Listed

Silver :

TSCA Inventory Status: Listed

Canada DSL: Listed

Tin :

TSCA Inventory Status: Listed

Canada DSL: Listed

Zinc :

TSCA Inventory Status: Listed

Canada DSL: Listed

Zinc Chloride :

TSCA Inventory Status: Listed

Canada DSL: Listed

Aniline Hydrochloride :

TSCA Inventory Status: Listed

Canada DSL: Listed

GHS Pictograms:



SECTION 16 - ADDITIONAL INFORMATION

General Use: Flux cored solder

HMIS Health Hazard: 2

HMIS Fire Hazard: 1

HMIS Reactivity: 1

HMIS Personal Protection: x

MSDS Creation Date: August 15, 2008

MSDS Revision Date: September 30, 2012

Disclaimer: The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Copyright© 1996-2011 Actio Corporation. All Rights Reserved.