

**SAFETY DATA SHEET**  
**Finished Product**



**Date-Issued: 6/7/2004**  
**SDS Ref. No: J-300/JT-004**  
**Date-Revised: 11/8/2017**  
**Revision No: 003**

**Butane Fuel Contained in**  
**J-300 & JT-004**

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Brand Name</b>	J-300/JT-004
<b>Product Description:</b>	Butane Torch and replacement cartridge containing Butane Fuel
<b>Product Code</b>	J-300/JT-004
<b>Marketer Contact Information:</b>	NTE Electronics, Inc. 44 Farrand Street Bloomfield, NJ 07003 973-748-5089
<b>Emergency Phone:</b>	CHEMTREC 800-424-9300

**SECTION 2. HAZARDS IDENTIFICATION**

<b>Most Important Hazards</b>	None
<b>Adverse Human Health Effects</b>	None
<b>Environmental Effects</b>	None
<b>Physical and Chemical Hazards</b>	None

**SECTION 3. COMPOSITION / INFORMATION OF INGREDIENTS**

<b>Substance or Preparation</b>	Substance
<b>Chemical Name</b>	Acrylonitrile-Butadiene-Styrene Copolymer
<b>Content</b>	> 98% (Additives ≤ 2%)
<b>Formula</b>	(C <sub>3</sub> H <sub>3</sub> N, C <sub>4</sub> H <sub>6</sub> , C <sub>8</sub> H <sub>8</sub> ) <sub>x</sub>
<b>CAS No.</b>	9003-56-9
<b>Impurities Contributing to Hazard</b>	None

**SECTION 4. FIRST-AID MEASURES**

<b>Inhalation</b>	In case of gases evolving from melted resin, move subject to fresh air. Treat symptomatically.
<b>Skin Contact</b>	In case of pellets or powder, wash with water. In case of melt, wash affected skin area and clothing with plenty of (soap and) water. Seek medical advice.
<b>Eye Contact</b>	In case of pellets or powder, flush with plenty of water for at least 15 minutes. Seek medical advice if any dust particles still remain. In case of gases evolving from melted resin of high temperature, flush with plenty of water for at least 15 minutes. Seek medical advice if necessary.
<b>Ingestion</b>	Induce vomiting. Rinse mouth with water. Seek medical advice if necessary.

**SECTION 5. FIRE FIGHTING MEASURES**

<b>Extinguishing Media</b>	Water, Foam, Dry chemical powder.
<b>Special Fire-Fighting Procedure</b>	Self contained breathing apparatus
<b>Fire and Explosion Hazards</b>	None

## SECTION 6. ACCIDENTAL RELEASE MEASURES

<b>Methods for Cleaning Up</b>	Recovery if not contaminated or Disposal
<b>Personal Precautions</b>	Pellets or powder remained on ground may cause slipping
<b>Environmental Precautions</b>	Gather pellets and powder thoroughly to avoid birds or fishes taking from draining water.

## SECTION 7. HANDLING AND STORAGE

<b>Handling</b>	Prevent from fire around handling area. Maintain good housekeeping standards to prevent accumulation of dust. To avoid dust explosion resulting from the existence of powder, electrostatics eliminators and grounding should be fixed to such equipment as air transferring pipes, bag filters and hoppers. Use electrically conductive filters for bag filters.
<b>Storage</b>	Keep the materials at a cool dry place. Protect from direct sunlight, rain and violent temperature fluctuation. Fire is inhibited around storage area.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Threshold Limit Value</b>	Not determined
<b>Ventilation</b>	Necessary to exclude dust, fumes and gases.

### Personal Protection

<b>Eyes</b>	Wear safety glasses for general purpose. Wear chemical goggles for cleaning molding machines.
<b>Respiratory</b>	Wear masks for cleaning molding machines.
<b>Gloves</b>	Necessary for handling melted resin.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Off white pellets
<b>Melting Temperature</b>	Softening above +100°C
<b>Solubility</b>	Insoluble in water.
<b>Specific Gravity</b>	1.03 to 1.10

## SECTION 10. STABILITY AND REACTIVITY

<b>Flammability</b>	Yes
<b>Flash Point</b>	+404°C
<b>Auto-ignition Temperature</b>	+466°C
<b>Reactivity with Water</b>	No
<b>Stability</b>	Stable and non-reactive under normal handling and storage condition.
<b>Dust Explosion</b>	Possible if powder exists. Explosion data for powder (< 145 mesh) Lower explosion limit 45 g/m <sup>3</sup> Minimum ignition energy 3.6 mJ Maximum explosion pressure 7 x 10 <sup>5</sup> Pa Maximum pressure increase rate 3.2 x 10 <sup>3</sup> Pa/S
<b>Thermal Decomposition Gases</b>	CO, HCN, AN, SM and NO
<b>Combustion Energy</b>	3.53 x 10 <sup>7</sup> J/kg (8424 Kcal/kg)

## SECTION 11. TOXICOLOGICAL INFORMATION

<b>Irritation</b>	Fumes or vapors generated from decomposing resin may be irritant to eyes.
<b>Acute Oral Toxicity (LD50)</b>	Not determined
<b>Mutagenicity</b>	Not determined

**SECTION 12. ECOLOGICAL INFORMATION**

<b>Conclusion/Summary</b>	To void being taken by ocean species or birds, disposal of the waste to the ocean and water sources is inhibited.
---------------------------	---

**SECTION 13. DISPOSAL CONSIDERATIONS**

<b>Conclusion/Summary</b>	Controlled incineration o landfill according to local, state or national laws and regulations concerning health and pollution. Inadequate incineration may generate toxic gases such as CO, HCN, AN and SM.
---------------------------	---

**SECTION 14. TRANSPORT INFORMATION**

<b>Conclusion/Summary</b>	Not classified as a dangerous good under transport regulations.
---------------------------	---

**SECTION 15. REGULATORY INFORMATION**

<b>Conclusion/Summary</b>	Not available
---------------------------	---------------

**SECTION 16. OTHER INFORMATION****Further Information**

This information above is believed to be accurate and represents the best information currently available to us. However, neither NTE nor any of its subsidiaries make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.