

Super Bright LEDs

S E L E C T O R G U I D E



Features:

- NEW*** • ***Now includes 8mm and 10mm sizes in addition to 1.8mm, 3mm and 5mm!***
- ***All plastic mold with water clear lens!***
- ***Complete selection including blue and white!***

***Ask your NTE distributor
for price and availability!***

See reverse for complete specs.

NTE[®]
ELECTRONICS, INC.
www.nteinc.com

NTE Type Number	Individual Package Size	Typical Viewing Angle (°)	Viewed Color	Typical Luminous Intensity (mcd) I_V	Typical Forward Voltage Drop (Volts) V_F	Maximum Reverse Breakdown Voltage (Volts) V_R	Maximum DC Forward Current (mA) I_F	Maximum Power Dissipation (mW) P_D
3137	T-3/4 (1.8mm)	24	Super Red	1500	2.0	5	25	100
3138	T-3/4 (1.8mm)	24	Super Red	1200	1.66	5	25	110
3136	T-3/4 (1.8mm)	24	Super Orange	1300	2.0	5	25	100
3134	T-3/4 (1.8mm)	24	Super Yellow	1300	2.0	5	25	100
30009	T-3/4 (1.8mm)	20	Super Green	100	2.2	5	25	105
3133	T-3/4 (1.8mm)	24	Super Yellow/Green	900	2.2	5	25	100
3132	T-3/4 (1.8mm)	24	Super High-Eff Yellow Green	500	2.15	5	25	84
3139	T-3/4 (1.8mm)	24	Super Blue	1500	3.5	4	25	120
30034	T-1 (3mm)	19	Super Deep Red	2000	2.5 Max	5	25	110
30035	T-1 (3mm)	10	Super Amber	2500	2.4 Max	5	25	100
30033	T-1 (3mm)	10	Super Orange	2500	2.6 Max	5	25	100
30032	T-1 (3mm)	10	Super Yellow	2500	2.4 Max	5	25	100
30031	T-1 (3mm)	14	Super Pure Green	5000	4.0 Max	5	30	120
30030	T-1 (3mm)	14	Super Yellow/Green	1600	2.4 Max	5	25	100
30036	T-1 (3mm)	15	Super Blue	3000	4.0 Max	5	30	120
30044	T-1 (3mm)	30	Super White	7000	4.0 Max	5	30	120
30041	T-1 3/4 (5mm)	12	Super Deep Red	3500	2.5 Max	5	25	110
30040	T-1 3/4 (5mm)	12	Super Orange	5500	2.6 Max	5	25	100
30042	T-1 3/4 (5mm)	12	Super Amber	5500	2.4 Max	5	25	100
30039	T-1 3/4 (5mm)	12	Super Yellow	7000	2.6 Max	5	30	100
30038	T-1 3/4 (5mm)	15	Super Pure Green	10500	4.0 Max	5	30	120
30037	T-1 3/4 (5mm)	12	Super Yellow/Green	2500	2.4 Max	5	25	100
30043	T-1 3/4 (5mm)	12	Super Blue	3500	4.0 Max	5	30	120
30045	T-1 3/4 (5mm)	22	Super White	16000	4.0 Max	5	30	120
30053	8mm	25	Super Yellow Green	1600	2.2	5	25	100
30054	8mm	30	Super Light Green	4500	3.5	4	25	120
30055	8mm	25	Super Orange	3600	2.0	5	25	100
30056	8mm	25	Super Light Red	3600	2.0	5	25	100
30057	8mm	30	Super Deep Red	2200	1.86	5	25	110
30058	8mm	35	Super Blue	1500	3.5	4	25	120
30059	8mm	30	Super White	4000	3.5	4	25	120
30065	T- 3 1/4 (10mm)	40	Super Yellow Green	1300	2.2	5	25	100
30066	T- 3 1/4 (10mm)	40	Super Light Green	3500	3.5	4	30	120
30067	T- 3 1/4 (10mm)	40	Super Orange	2000	2.0	5	25	100
30068	T- 3 1/4 (10mm)	40	Super Light Red	2000	2.0	5	25	100
30069	T- 3 1/4 (10mm)	40	Super Deep Red	3000	1.86	5	25	110
30070	T- 3 1/4 (10mm)	40	Super Blue	1200	3.5	4	25	120
30071	T- 3 1/4 (10mm)	40	Super White	4000	3.5	4	25	120

**Ask your NTE distributor for price and availability!
For more information please visit www.nteinc.com**

Distributed By:



44 Farrand Street
Bloomfield, NJ 07003-2597
Fax: 973-748-6224
For more information, call 973-748-5089
or visit www.nteinc.com