





Selector Guide

Special Function Devices

Series	R66	RLY300	R67	R68
				
Features	<ul style="list-style-type: none"> • For Duplex Loads • Transient Protection • LED Indicates Output Relay Status • 8-Pin Octal Type Plug 	<ul style="list-style-type: none"> • For Duplex Loads • Transient Protection • LED Indicates Output Relay Status • 8-Pin Octal Type Plug 	<ul style="list-style-type: none"> • Monitors AC Single Phase and DC Voltages • User-Adjustable Pick-Up and Drop-Out Settings • LED Indicates Output Relay Status • 8-Pin Octal Type Plug 	<ul style="list-style-type: none"> • Protection Against Phase Loss, Phase Reversal, Phase Unbalance, and Undervoltage • User Selectable Phase Unbalance and Overvoltage Settings • User Adjustable Time Delay Drop-Out on Undervoltage • LED Indicates Normal and Fault Conditions • Compatible With Wye or Delta Systems • 8-Pin Octal Type Plug
Mode of Operation	Alternating	Alternating	Voltage Monitoring	Phase Monitoring
Contact Arrangement	SPDT, DPDT (Cross-Wired)	SPDT, DPDT (Cross-Wired)	DPDT	SPDT
Contact Ratings	10A @ 30VDC/240VAC	10A @ 30VDC/240VAC	10A @ 30VDC/240VAC	10A @ 30VDC/240VAC
Input Voltage	120, 240VAC	24VAC	24, 120VAC/24VDC	208-480VAC
Response Time				1-300sec adj (Restart) 100ms fixed (D/O Phase Loss) 2sec fixed (D/O Phase Unbal) 0.1-20sec adj (D/O Undervltg)
Operate	-	-	50ms	
Release	-	-	50ms	
Page	72	72	73	74