



16 Hex

.512 (13.0) Dia.

.512 (13.0) Dia.

.476 (12.1)

Recommended Mounting Hole

.110 (2.8)

1/2-28UNEF-2A

.433 (11.0)

.748 (19.0)

1.280 (32.5) Ref.

.610 (15.5) Dia.

.630 (16.0) Dia.

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
  2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
  3. Phosphor Bronze
  4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
  5. DELRIN

RoHS Compliant

7	Hex Nut	Note 1	Note 2	1	Dimensions are in Inches Unless Otherwise Specified Tolerances 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	Part No.	<div style="text-align: center; font-size: 2em; font-weight: bold;">NTE Electronics</div>			
7	Lock Washer	Note 1	Note 2	1				Approved	Date 7-7-2010	Title BNC Female to Female Bulkhead Isolated Adaptor
6	Housing	Note 1	Note 2	1				Checked	Date 7-7-2010	Drawing No. 06-B014
5	Body	Note 1	Note 2	1				Drawn	Date 7-7-2010	File No.
4	Insulator	Note 5	Natural	1						
3	Contact Pin	Note 3	Note 4	2						
2	Insulator	Note 5	Natural	1						
1	Body	Note 1	Note 2	1						
No	Description	Material	Finish	Q'ty	Drawing No.	Scale	2.5/1	Issue	A	

B

A

F

E

D

C

B

A

1

2

3

4

5

6

7

8

1

2

3

4

5

6

7

8