



NOTES: Finish (Plating Thickness in Micro-inches)  
 1. Brass  
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick  
 3. Phosphor Bronze  
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 5. TEFLON

RoHS Compliant

Crimped Ferrule  
 Hex Crimp Size .255 (6.5)  
 Crimped Contact Pin  
 Hex Crimp Size .068 (1.7)

Dimensions are in Inches				Part No.	
Unless Otherwise Specified Tolerances				Approved	
0.5-6 = ±0.2				Date	
6-30 = ±0.4				12-13-2018	
30-120 = ±0.6				Checked	
120-315 = ±1				Date	
315-1000 = ±1.6				12-13-2018	
1000-2000 = ±2.4				Drawn	
				Date	
				12-13-2018	

<b>NTE Electronics</b>		Title	BNC Crimp Jack (For RG-59, 62)
		Drawing No.	06-B020
		File No.	
		Part No.	

No.	Description	Material	Finish	Q'ty	Drawing No.
5	Ferrule	Note 1	Note 2	1	
4	Contact Pin	Note 3	Note 4	1	
3	Insulator	Note 5	Natural	1	
2	Lock Ring	Iron	Note 2	1	
1	Body	Note 1	Note 2	1	

A

A