



Recommended Cable Stripping Dim's

NOTES: Finish (Plating Thickness in Micro-inches)  
 1. Brass  
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick  
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 4. TEFLON

RoHS Compliant

Crimped Contact Pin  
 Hex Crimp Size .068 (1.7)

12	Contact Pin	Note 1	Note 3	1	
11	Hex Nut	Note 1	Note 2	1	
10	Washer	Note 1	Note 2	1	
9	Gasket	Silicone	Red	1	
8	Top Hat	Note 1	Note 2	1	
7	Washer	Note 1	Note 2	1	
6	Spring	SK5	Note 2	1	
5	Retainer Ring	Note 1	Note 2	1	
4	Gasket	Rubber	Red	1	
3	Contact Pin	Note 1	Note 4	1	
2	Insulator	Note 5	Natural	1	
1	Body	Note 1	Note 2	1	
No.	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches  
 Unless Otherwise Specified  
 Tolerances  
 0.5-6 = ±0.2  
 6-30 = ±0.4  
 30-120 = ±0.6  
 120-315 = ±1  
 315-1000 = ±1.6  
 1000-2000 = ±2.4

Part No.	
Approved	Date 12-14-2018
Checked	Date 12-14-2018
Drawn	Date 12-14-2018

<b>NTE Electronics</b>	
Title BNC Clamp Plug (For RG-174, 188A, 316, LMR100)	
Drawing No. 06-B022	
File No.	