



Recommended Cable Stripping Dim's

Crimped Ferrule
Hex. Crimp Size .213 (5.4)
Contact Pin to Solder

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
 2. Albaloy Plating (Copper-Tin-Zinc) Pl. 80 Min, Thick
 3. Gold Pl. 5 Min Thick over Copper Pl. 50 Min. Thick
 4. Teflon
 5. Passivated

RoHS Compliant

10	Ferrule	Copper	Note 2	1	
9	Nut		Note 1	Note 2	1
8	Barrel		Note 1	Note 2	1
7	Contact Pin		Note 1	Note 3	1
6	Retainer Ring	SUS 304	Note 5		1
5	Gasket	Silicone	Red		1
4	Contact Body		Note 1	Note 2	1
3	Insulator		Note 4	Natural	1
2	Body		Note 1	Note 2	1
1	Shell		Note 1	Note 2	1

Dimensions are in Inches				Part No.	
Unless Otherwise Specified Tolerances				Approved	
0.5-6	=	±0.2	Date 12-14-2018		
6-30	=	±0.4	Checked		
30-120	=	±0.6	Date 12-14-2018		
120-315	=	±1	Drawn		
315-1000	=	±1.6	Date 12-14-2018		
1000-2000	=	±2.4			
No.	Description	Material	Finish	Q'ty	Drawing No.
1					Scale 2.5/1 Issue A

NTE Electronics

Title N R/A Crimp Plug
(For RG-58, 58A, 58C, 141, LMR195)

Drawing No. 06-N007

File No.