



NOTES: Finish (Plating Thickness in Micro-inches)  
 1. Brass  
 2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 4. Teflon  
 5. Passivated

8	Heat Shrink Tubing		Black	1	
7	Ferrule	Note 1	Note 2	1	
6	Contact Pin	Note 1	Note 3	1	
5	Gasket	Silicone	Red	1	
4	Retaining Ring	SUS 304	Note 5	1	
3	Insulator	Note 4	Natural	1	
2	Body	Note 1	Note 2	1	
1	Shell	Note 1	Note 2	1	
No	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches  
 Unless Otherwise Specified  
 Tolerances  
 0.5-6 = ±0.2  
 6-30 = ±0.4  
 30-120 = ±0.6  
 120-315 = ±1  
 315-1000 = ±1.6  
 1000-2000 = ±2.4

Part No.									
Approved	Date 12-8-2015								
Checked	Date 12-8-2015								
Drawn	Date 12-8-2015								
No	Description	Material	Finish	Q'ty	Drawing No.	Scale	5/1	Issue	A2

**NTE Electronics**

Title  
SMA Crimp Plug  
(For RG-174, 188A, 316, LMR100)

Drawing No. 06-S001

File No.