



- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
 2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 3. Beryllium Copper
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. Teflon
 6. Passivated

RoHS Compliant

Crimped Ferrule
Hex Crimp Size .213 (5.41)

					Dimensions are in Inches				Part No.		NTE Electronics		
					Unless Otherwise Specified Tolerances				Approved				Title
7	Ferrule	Copper	Note 2	1					Date		SMA Reverse Polarity Crimp Plug (For RG-58, 58A, 58C, 141, LMR195)		
6	Contact Pin	Note 3	Note 4	1	0.5-6 = ±0.2				4-19-2013				
5	Gasket	Silicone	Red	1	6-30 = ±0.4				Checked		Drawing No. 06-S002		
4	Retaining Ring	SUS 304	Note 6	1	30-120 = ±0.6				Date				
3	Insulator	Note 5	Natural	1	120-315 = ±1				4-19-2013		File No.		
2	Body	Note 1	Note 2	1	315-1000 = ±1.6				Date				
1	Shell	Note 1	Note 2	1	1000-2000 = ±2.4				4-19-2013				
No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	4/1	Issue	A				