



NOTES: Finish (Plating Thickness in Micro-inches)

1. Brass
2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
3. Phosphor Bronze
4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
5. Teflon

Crimped Ferrule
Hex Crimp Size .213 (5.41)
Crimped Contact Pin
Hex Crimp Size .068 (1.7)

RoHS Compliant

No	Description	Material	Finish	Q'ty	Drawing No.
10	Ferrule	Copper	Note 2	1	
9	Contact Pin		Note 3	Note 4	1
8	Shell		Note 1	Note 2	1
7	Gasket	Rubber	Red	1	
6	Retainer Ring		Note 1	Note 2	1
5	Ring	DELTRIN	Natural	1	
4	Washer		Note 1	Note 2	1
3	Barrel		Note 1	Note 2	1
2	Insulator		Note 5	Natural	1
1	Body		Note 1	Note 2	1

Dimensions are in Inches
Unless Otherwise Specified
Tolerances
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

Part No.	
Approved	Date 6-6-2013
Checked	Date 6-6-2013
Drawn	Date 6-6-2013

NTE Electronics	
Title	TNC Reverse Polarity Crimp Plug (For RG-58C/U, 58U)
Drawing No.	06-T004
File No.	