



**ELECTRONICS, INC.**  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089

## NTE1024 Integrated Circuit Module – Hybrid, Audio Power Amplifier

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Maximum Supply Voltage,  $V_{CCmax}$  ..... 35V  
 Operating Case Temperature,  $T_C$  .....  $+85^\circ\text{C}$   
 Storage Temperature Range,  $T_{stg}$  .....  $-30^\circ$  to  $+100^\circ\text{C}$   
 Available Load Shorting Time ( $V_{CC} = 25\text{V}$ ,  $P_O = 5\text{W}$ ,  $R_L = 8\Omega$ ,  $f = 50\text{Hz}$ ),  $t_s$  ..... 2sec

**Recommended Operating Conditions:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Supply Voltage,  $V_{CC}$  ..... 25V  
 Load Resistance,  $R_L$  .....  $8\Omega$

**Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$ ,  $V_{CC} = 25\text{V}$ ,  $R_L = 8\Omega$ ,  $R_g = 600\Omega$ ,  $f = 1\text{kHz}$ ,  $R_{NF} = 3\text{k}\Omega$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Current	$I_{CCO}$		–	–	50	mA
Output Power	$P_O$	THD = 2%	6.5	8.0	–	W
Voltage Gain	VG	$P_O = 100\text{mW}$	34	35	36	dB
Total Harmonic Distortion	THD	$P_O = 100\text{mW}$	–	–	1.0	%
Input Impedance	$r_i$	$P_O = 100\text{mW}$	15	40	–	$\text{k}\Omega$
Output Impedance	$r_o$	$P_O = 100\text{mW}$	–	0.2	–	$\Omega$
High Level Cut-Off Frequency	$f_{CH}$	$V_i = 50\text{mV}$ , $-3\text{dB}$	50	–	–	kHz
Low Level Cut-Off Frequency	$f_{CL}$	$V_i = 50\text{mV}$ , $-3\text{dB}$	–	–	30	Hz
Power Bandwidth	PBW	THD = 2%, $\pm 3\text{dB}$	30 to 30k			Hz
Output Noise Voltage	$V_{NO}$	$R_g = 10\text{k}\Omega$	–	–	4	mV

**Pin Connection Diagram**  
(Front View)

