



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE1166 Integrated Circuit Module, Hybrid, Audio Output, 5.8W for Car Radio & CB

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Power Supply Voltage, V_{CC}	18V
Power Dissipation ($T_C = +75^\circ\text{C}$), P_D	5.8W
Operating Temperature Range, T_{opr}	-20° to $+75^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55° to $+125^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 13.2\text{V}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Quiescent Current	I_Q	$V_{IN} = 0$	-	28	70	mA
Voltage Gain (Closed Circuit)	G_{VC}	$f = 1\text{kHz}$, $R_L = 4\Omega$, $R_N = 68\Omega$	52	-	58	dB
Power Output	P_{out}	$f = 1\text{kHz}$, $R_L = 4\Omega$, THD = 10%	4.5	5.8	-	W
Total Harmonic Distortion	THD	$f = 1\text{kHz}$, $R_L = 4\Omega$, $P_{out} = 0.5\text{W}$	-	0.6	2.0	%
Output Noise Voltage	V_{NO}	$R_g = 10\text{k}\Omega$, $R_L = 4\Omega$	-	1.5	5.0	mV
Input Resistance	R_{in}	$f = 1\text{kHz}$	-	25	-	$\text{k}\Omega$

Pin Connection Diagram
(Front View)



