



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE1425 Integrated Circuit Capstan Servo Control Circuit for VCR

Features:

- Phase Control Circuit
- Speed Control Circuit
- Capstan FG Divider Ratio Change Circuit
- Sample Hold System Speed Control
- Supply Voltage, Either 9V or 12V

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$, unless otherwise specified)

Supply Voltage, V_{CC}	14V
Power Dissipation, P_D	470mW
Operating Temperature Range, T_{opg}	-20° to $+70^\circ\text{C}$
Storage Temperature Range, T_{stg}	-40° to $+150^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 12\text{V}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Circuit Current	I_1		16	-	34	mA
Sensitivity (PG Amp In)	$S_{(1)}$		50	-	-	mV _{o-p}
(In)	$S_{(2)}$		7	-	-	V _{o-p}
Reference Voltage	$V_{REF(1)}$		2.7	-	3.7	V
Voltage High Level (S/H1)	$V_{OH(1)}$		9	-	-	V
Voltage Low Level (S/H1)	$V_{OL(1)}$		-	-	600	mV
Sensitivity Output (FG Amp In)	$S_{(3)}$		100	-	-	mV _{p-p}
(FF 2 Switch)	$S_{(4)}$		5	-	-	V
Reference Voltage	$V_{REF(2)}$		2.7	-	3.7	V
Voltage High Level (S/H2)	$V_{OH(2)}$		9	-	-	V
Voltage Low Level (S/H2)	$V_{OL(2)}$		-	-	600 mV	

Pin Connection Diagram

