



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089

NTE1817 Integrated Circuit Module, AF PO, 20W, Dual Power Supply

Features:

- Muting Curcuit to Cut Off Pop Noise

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Maximum Supply Voltage, V_{CCmax} $\pm 34.5\text{V}$
 Junction Temperature, T_J $+150^\circ\text{C}$
 Operating Case Temperature, T_C $+125^\circ\text{C}$
 Storage Temperature Range, T_{stg} -30° to $+125^\circ\text{C}$
 Thermal Resistance, Junction-to-Case, R_{thJC} 2.6°C/W
 Available Time for Load Shorted ($V_{CC} = \pm 23\text{V}$, $R_L = 8\Omega$, $f = 50\text{Hz}$, $P_O = 20\text{W}$), t_s 2sec

Recommended Operating Conditions: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Recommended Supply Voltage, V_{CC} $\pm 23\text{V}$
 Load Resistance, R_L 8Ω

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = \pm 23\text{V}$, $R_L = 8\Omega$ (Non-Inductive Load), $R_g = 600\Omega$, $V_G = 40\text{dB}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Quiescent Current	I_{CCO}	$V_{CC} = \pm 28\text{V}$	20	40	100	mA
Output Power	P_O	THD = 0.4%, $f = 20\text{Hz}$ to 20kHz	20	-	-	W
		$V_{CC} = \pm 20\text{V}$, THD = 1%, $R_L = 4\Omega$, $f = 1\text{kHz}$	20	-	-	W
Total Harmonic Distortion	THD	$P_O = 1\text{W}$, $f = 1\text{kHz}$	-	-	0.3	%
Frequency Response	f_L, f_H	$P_O = 1\text{W}$, -3dB	20 to 50k			Hz
Input Resistance	r_i	$P_O = 1\text{W}$, $f = 1\text{kHz}$	-	55	-	k Ω
Output Noise Voltage	V_{NO}	$V_{CC} = \pm 28\text{V}$, $R_g = 10\text{k}\Omega$	-	-	1.2	mV _{rms}
Middle-Point Voltage	V_N	$V_{CC} = \pm 28\text{V}$	-70	0	+70	mV

Note 1. For power supply at the time of test, use a constant-voltage power supply unless otherwise specified.

Pin Connection Diagram
(Front View)

