



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE2345 (NPN) & NTE2346 (PNP) Silicon Complementary Transistors General Purpose Darlington, Power Amplifier

Description:

The NTE2345 (NPN) and NTE2346 (PNP) are silicon complementary Darlington transistors in an SOT-82 type package designed for use in audio output stages and general amplifier and switching applications..

Features:

- High DC Current Gain: $h_{FE} = 750$ (Min) @ $I_C = 3A$, $V_{CE} = 3V$
- Junction Temperature to $+150^{\circ}C$

Absolute Maximum Ratings:

Collector–Emitter Voltage, V_{CEO}	120V
Collector–Base Voltage, V_{CBO}	120V
Emitter–Base Voltage, V_{EBO}	5V
Collector Current, I_C	
Continuous	6A
Peak ($t_p \leq 10ms$, $\delta \leq 0.1$)	10A
Base Current, I_B	150mA
Total Power Dissipation ($T_C = +25^{\circ}C$), P_D	60W
Junction Temperature, T_J	$+150^{\circ}C$
Storage Temperature Range, T_{stg}	-65° to $+150^{\circ}C$
Thermal Resistance, Junction–to–Case, R_{thJC}	2.08K/W
Thermal Resistance, Junction–to–Ambient, R_{thJA}	100K/W

Note 1. **NTE2346** is a **discontinued** device and **no longer available**.

Electrical Characteristics: ($T_J = +25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cutoff Current	I_{CBO}	$I_E = 0, V_{CBO} = 120V$	–	–	0.2	mA
		$I_E = 0, V_{CBO} = 120V, T_J = +150^{\circ}C$	–	–	2mA	mA
	I_{CEO}	$I_B = 0, V_{CEO} = 60V$	–	–	0.5	mA
Emitter Cutoff Current	I_{EBO}	$I_C = 0, V_{EBO} = 5V$	–	–	5	mA
DC Current Gain	h_{FE}	$I_C = 500mA, V_{CEO} = 3V$, Note 1	–	2700	–	
		$I_C = 3A, V_{CEO} = 3V$, Note 2	750	–	–	
		$I_C = 6A, V_{CEO} = 3V$, Note 2	–	400	–	

Note 2. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

