



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>

## NTE30091 Light Emitting Diode (LED) High-Efficiency Red + Green SOT-23 Surface Mount

**Features:**

- 3.0mm x 1.6mm SOT-23 SMT LED, 1.0mm Thickness
- High-Efficiency Red + Green
- Common Anode Pin Configuration

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

DC Forward Current, $I_F$	High-Efficiency Red .....	30mA
	Green .....	25mA
Peak Forward Current (Note 1), $I_{F(\text{peak})}$		50mA
Reverse Voltage, $V_R$		5V
Power Dissipation, $P_D$	High-Efficiency Red .....	90mW
	Green .....	84mW
Operating Temperature Range, $T_{opr}$		$-30^\circ$ to $+85^\circ\text{C}$
Storage Temperature Range, $T_{stg}$		$-40^\circ$ to $+85^\circ\text{C}$
Reflow Soldering (Preheat $+150^\circ$ to $+180^\circ\text{C}$ 60sec to 120sec, 10sec max)		$+260^\circ\text{C}$

Note 1. 1/10 Duty Cycle, 0.1ms Pulse Width.

**Electrical/Optical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Viewing Angle of Half Power	$2\theta_{1/2}$	$I_F = 20\text{mA}$	-	140	-	degrees
Luminous Intensity	$I_V$	$I_F = 20\text{mA}$ , Note 2	2.0	4.0	-	mcd
High-Efficiency Red						
Green			2.0	4.0	-	mcd
Forward Voltage	$V_F$	$I_F = 20\text{mA}$	-	2.05	2.60	V
High-Efficiency Red						
Green			-	2.15	2.80	V
Peak Emission Wave Length	$\lambda_P$	$I_F = 20\text{mA}$	-	625	-	nm
High-Efficiency Red						
Green			-	570	-	nm
Dominant Wavelength	$\lambda_d$ (HUE)	$I_F = 20\text{mA}$ , Note 3	-	618	-	nm
High-Efficiency Red						
Green			-	567	-	nm

Note 2. Tolerance: 30% measured with EXELTRON 2001

Note 3. The dominant wavelength,  $\lambda_d$ , is derived from the CIE Chromatic Diagram and represents the color of the device.

