



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE3033 Infrared Photodiode

Description:

The NTE3033 is a high output, high speed silicon photodiode mounted in a side-viewing plastic package with visible light cutoff filter.

Features:

- Visible Ray Cutoff Mold Type
- High Speed Response
- High Output Power

Applications:

- Optical Transmission
- Optic Receiver Modules

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)


Reverse Voltage, V_R 35V
 Power Dissipation, P_D 150mW
 Operating Temperature Range, T_{opr} -30° to $+70^\circ\text{C}$
 Storage Temperature Range, T_{stg} -40° to $+80^\circ\text{C}$
 Lead Temperature (During Soldering, 2mm from the package, 5sec Max.), T_L $+260^\circ\text{C}$

Electro-Optical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Open Circuit Voltage	V_{CC}	$E_V = 1000 \text{ lx}$, Note 1	-	0.4	-	V
Short Circuit Current	I_{SC}	$E_V = 1000 \text{ lx}$, Note 1	-	45	-	μA
Curve Factor	CF		0.55	-	-	-
Dark Current	I_D	$V_R = 10\text{V}$	-	-	30	nA
Capacitance	C_t	$V = 0\text{V}$, $f = 1\text{MHz}$	-	49	-	pF
Temperature Coefficient of V_{OC}	α_t		-	-2.2	-	$\text{mV}/^\circ\text{C}$
Temperature Coefficient of I_{SC}	β_t		-	0.18	-	$\%/^\circ\text{C}$
Spectral Sensitivity	λ		700 ~ 1050			nm
Peak Emission Wavelength	λ_P		-	1000	-	nm
Half Angle	$\Delta\theta$		-	± 70	-	deg

Note 1. Color temperature = 2856K standard Tungsten lamp.





* Denotes Cathode mark