



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE3144 thru NTE3147 Light Emitting Diode – 5mm

Features:

- All Plastic Mold Type ^w/Colored Diffused Lens:
 - NTE3144 (High Efficiency Red, AlGaP/GaAs)
 - NTE3145 (Yellow Green, GaInN/GaN)
 - NTE3146 (Yellow, AlInGaP/GaAs)
 - NTE3147 (Orange, AlInGaP/GaAs)

Absolute Maximum Ratings: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Power Dissipation, P_D		
NTE3144	100mW	
NTE3145	84mW	
NTE3146, NTE3147	90mW	
Continuous Forward Current, I_F		
NTE3144	20mA	
NTE3145, NTE3146	25mA	
NTE3147	30mA	
Peak Forward Current (0.1 ms pulse width, 1/10 duty cycle), I_{FM}		
NTE3144	100mA	
All Others	50mA	
Reverse Voltage, V_R	5V	
LED Junction Temperature, T_j	+100°C	
Operating Temperature Range, T_{opr}		
NTE3144	-40° to +85°C	
All Others	-25° to +85°C	
Storage Temperature Range, T_{stg}	-40° to +100°C	
Lead Temperature (During Soldering, 3sec max, 1.6mm below package base), T_L	+260°C	

Electrical Characteristics: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
View Angle of Half Power	2θ1/2	$I_F = 20\text{mA}$	-	40	-	Degree
NTE3144						
All Others						Degree
Forward Voltage	V_F	$I_F = 20\text{mA}$	-	2.00	2.50	V
NTE3144						
NTE3145				2.15	2.80	V
NTE3146				2.10	2.80	V
NTE3147				2.05	2.80	V
Reverse Current	I_R	$V_R = 5\text{V}$	-	-	10	µA

Note 1. Tolerance: 30%, measured using Exeltron 2001.

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Luminous Intensity NTE3144	I_V	$I_F = 20\text{mA}$, Note 1	80	100	-	mcd
NTE3145			50	80	-	mcd
NTE3146			35	80	-	mcd
NTE3147			40	60	-	mcd
Peak Emission Wavelength NTE3144	λ_p	$I_F = 20\text{mA}$	630	-	635	nm
NTE3145			-	570	-	nm
NTE3146			-	589	-	nm
NTE3147			-	625	-	nm
Dominate Wave Length NTE3145	$\lambda_d(\text{HUE})$	$I_F = 20\text{mA}$, Note 2	-	567	-	nm
NTE3146			-	585	-	nm
NTE3147			-	618	-	nm
Spectrum Width of Half Valve NTE3144	$\Delta\lambda$	$I_F = 20\text{mA}$	-	20	-	nm
NTE3145			-	30	-	nm
NTE3146			-	35	-	nm
NTE3147			-	45	-	nm
Terminal Capacitance NTE3145, NTE3146	C_t	$V = 0\text{V}$, $F = 1\text{MHz}$	-	7	-	pF
NTE3147			-	6	-	pF
Response Frequency	F_C		-	4	-	MHz

Note 2. The dominate wavelength, λ_d , is derived from the CIE Chromaticity Diagram and represents the color of the device.

