



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE6032 & NTE6033 Silicon Power Rectifier Diode 1000V, 40 Amp, DO5

Features:

- Fast Recovery Time
- Low Stored Charge
- Available in Cathode-to-Case (NTE6032) or Anode-to-Case (NTE6033) Style

Ratings and Characteristics:

Average Forward Current ($T_C = +75^\circ\text{C Max}$), $I_{F(AV)}$	40A
Maximum Repetitive Peak Reverse Voltage ($T_J = -40^\circ$ to $+125^\circ\text{C}$), V_{RRM}	1000V
Maximum Non-Repetitive Peak Reverse Voltage ($T_J = +25^\circ$ to $+125^\circ\text{C}$, $t_p \leq 5\text{ms}$), V_{RSM} ..	1250V
Maximum Reverse Current (At Rated V_R), I_R	
$T_J = +25^\circ\text{C}$	0.1mA
$T_J = +125^\circ\text{C}$	10mA
Maximum Forward Surge Current, I_{FSM}	
50Hz	700A
60Hz	730A
Fusing Current, I^2t	
50Hz	2450A ² s
60Hz	2200A ² s
Fusing Current, $I^2\sqrt{t}$	34500A ² \sqrt{s}
Operating Junction Temperature range, T_J	-40° to $+125^\circ\text{C}$
Storage Temperature range, T_{stg}	-40° to $+150^\circ\text{C}$
Thermal Resistance, Junction-to-Case (DC Operation), R_{thJC}	0.6 $^\circ\text{C/W}$
Thermal Resistance, Case-to-Sink (Surface flat, smooth, and greased), R_{thCS}	0.25 $^\circ\text{C/W}$
Maximum Mounting Torque (Non-lubricated threads), T	30 (3.3) in•lb (m•N)

Electrical Specifications:

Parameter	Symbol	Test Conditions		Rating	Unit
Maximum Average Forward Current	$I_F (AV)$	180° sinusoidal condition, $T_C = +75^\circ C$ Max		40	A
Maximum Peak One-Cycle Non-Repetitive Surge Current	I_{FSM}	$t = 10ms$	Half sinewave current, rated V_{RRM} reapplied, initial $T_J = +125^\circ C$	400	A
		$t = 8.3ms$		420	A
		$t = 10ms$	Half sinewave current, no voltage reapplied, initial $T_J = +125^\circ C$	475	A
		$t = 8.3ms$		500	A
Maximum I^2t for Fusing	I^2t	$t = 10ms$	Rated V_{RRM} reapplied, initial $T_J = +125^\circ C$	800	A^2s
		$t = 8.3ms$		730	A^2s
Maximum I^2t for Individual Device Fusing	I^2t	$t = 10ms$	No voltage reapplied, initial $T_J = +125^\circ C$	1150	A^2s
		$t = 8.3ms$		1050	A^2s
Maximum $I^2\sqrt{t}$	$I^2\sqrt{t}$	$t = 0.1$ to $10ms$, no voltage reapplied, Note 1		11500	$A^2\sqrt{t}$
Maximum Peak Forward Voltage	V_{FM}	$T_J = +25^\circ C$, $I_{FM} = 125A$		1.95	V
Maximum Reverse Recovery Time	t_{rr}	$T_J = +25^\circ C$, $I_F = 1A$ to $V_R = 30V$, $-di_F/dt = 100A/\mu s$		350	ns
		$T_J = +25^\circ C$, $I_F = 125A$, $-di_F/dt = 25A/\mu s$		1000	ns
Maximum Reverse Recovery Charge	Q_{RR}	$T_J = +25^\circ C$, $I_F = 1A$ to $V_R = 30V$, $-di_F/dt = 100A/\mu s$		3100	nC
		$T_J = +25^\circ C$, $I_F = 125A$, $-di_F/dt = 25A/\mu s$		6000	nC

Note 1. I^2t for time $t_x = I^2\sqrt{t} \cdot \sqrt{t_x}$.

