



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089

NTE7073 Integrated Circuit Hybrid Switching Regulator

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

| | |
|---|-------------------------------------|
| TR1 Collector–Emitter Voltage (Note 1), V_{CEX} | 500V |
| Applying Voltage, Pin4–2, V_{2-4} | 12V |
| Applying Voltage, Pin2–5, V_{2-5} | 12V |
| Applying Voltage, Pin5–9, V_{5-9} | 30V |
| Applying Voltage, Pin7–6, V_{7-6} | 5V |
| TR1 Collector Current, $I_{C(TR1)}$ | |
| Continuous | 10A |
| Pulsed | 20A |
| TR4 Collector Current, $I_{C(TR4)}$ | 500mA |
| D2 Forward Current, $I_{IN(D2)}$ | 500mA |
| D3 Forward Current, $I_{IN(D3)}$ | 100mA |
| Maximum Power Dissipation (Note 2), P_D | |
| No Fin | 3.2W |
| $T_{C1} = +100^\circ\text{C}$ | 2.7W |
| TR1 Junction Temperature, T_J | $+150^\circ\text{C}$ |
| Frame Temperature Range (Operating, Note 3), T_{C2} | -20° to $+125^\circ\text{C}$ |
| Storage Temperature Range, T_{stg} | -30° to $+125^\circ\text{C}$ |
| Maximum Output Current ($V_O = 115\text{V}$), I_O | 1.7A |

Note 1. Reference: $V_{CEO} = 400\text{V}$ Min

Note 2. T_{C1} denotes the temperature of resin beneath the Power Transistor.

Note 3. T_{C2} denotes the internal frame temperature. Recommended $T_{C2} = +100^\circ\text{C}$.

Electrical Characteristics (TR1 Characteristics): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-------------------------------------|------------------|--|-----|-----|------|--------------------|
| Saturation Voltage | $V_{CE(sat)}$ | $I_C = 8\text{A}, I_B = 1.2\text{A}$ | – | – | 0.5 | V |
| | $V_{BE(sat)}$ | $I_C = 6\text{A}, I_B = 1.2\text{A}$ | – | – | 1.5 | V |
| Collector Cutoff Current | I_{CBO} | $V_{CE} = 500\text{V}, V_{BE} = 1.5\text{V}$ | – | – | 1.8 | mA |
| DC Current Gain | h_{FE} | $I_C = 1\text{A}, V_{CE} = 4\text{V}$ | 15 | – | 40 | |
| Power Transistor Thermal Resistance | $R_{\theta JC2}$ | Between Junction and Internal Frame | – | 0.7 | – | $^\circ\text{C/W}$ |
| Switching Time | t_s | | – | – | 10.0 | μs |
| | t_f | | – | – | 0.6 | μs |

Pin Connection Diagram
(Front View)

