



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>



NTE7206 Integrated Circuit Triple Video Output Amplifier

Description:

The NTE7206 includes three video output amplifiers in one plastic 9-Lead SIP medium power package, using high-voltage DMOS technology, and is intended to drive the three cathodes of a color CRT directly. To obtain maximum performance, the amplifier should be used with black-current control.

Features:

- Typical Bandwidth of 5.5MHz for an Output Signal of 60V (p-p)
- High Slew Rate of 900V/ μ s
- No External Components Required
- Very Simple Application
- Single Supply Voltage of 200V
- Internal Reference Voltage of 2.5V
- Fixed Gain of 50
- Black-Current Stabilization (BCS) Circuit
- Thermal Protection.

Absolute Maximum Ratings: (Voltages measured with respect to Pin4 (GND) unless otherwise specified)

Supply Voltage, V_{DD}	250V
Input Voltage at Pin1 to Pin3, V_i	12V
Measurement Output Voltage, $V_{o(m)}$	6V
Cathode Output Voltage, $V_{o(c)}$	V_{DD}
Junction Temperature Range, T_j	-20° to +150°C
Storage Temperature Range, T_{stg}	-55° to +150°C
Electrostatic Handling, V_{es}	
Human Body Model (HBM)	2000V
Machine Model (MM)	300V
Thermal Resistance, Junction-to-Ambient, $R_{th(JA)}$	56K/W
Thermal Resistance, Junction-to-Fin (Note 1), $R_{th(J-FIN)}$	11K/W
Thermal Resistance, Heatsink-to-Ambient, $R_{th(H-A)}$	18K/W

Note 1. An external heatsink is necessary.

Recommended Operating Conditions:

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Voltage	V_{DD}		180	-	210	V
Operating Range	T_j		-20	-	+150	°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{DD} = 200\text{V}$, $V_{O(c1)} = V_{O(c2)} = V_{O(c3)} = 1/2V_{DD}$, $C_L = 10\text{ pF}$ (C_L consists of parasitic and cathode capacitance), $R_{th(H-A)} = 18\text{K/W}$ unless otherwise specified).

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Quiescent Supply Current	I_q		5.9	6.9	7.9	mA
Internal Reference Voltage (input stage)	$V_{ref(int)}$			2.5		V
Input Resistance	R_i			3.6		k Ω
Gain of Amplifier	G		47.5	51.0	55.0	
Gain Difference	ΔG		-2.5	0	+2.5	
Nominal Output Voltage at Pin7, Pin8 and Pin9 (DC Value)	$V_{O(c)}$	$I_i = 0\mu\text{A}$	116	129	142	V
Differential Nominal Output Offset Voltage between Pin7 and Pin8, Pin8 and Pin9 and Pin9 and Pin7 (DC Value)	$\Delta V_{O(c)(offset)}$	$I_i = 0\mu\text{A}$		0	5	V
Output Voltage Temperature Drift at Pin7, Pin8 and Pin9	$\Delta V_{O(c)(T)}$			-10		mV/K
Differential Output Offset Temperature Drift between Pin7 and Pin8, Pin8 and Pin9 and Pin7 and Pin9	$\Delta V_{O(c)(T)(offset)}$			0		mV/K
Offset Current of Measurement Output	$I_{O(m)(offset)}$	$I_{O(c)} = 0\mu\text{A}$, $1.5\text{V} < V_i < 5.5\text{V}$, $3\text{V} < V_{O(m)} < 6\text{V}$	-50		+50	μA
Linearity of Current Transfer	$\Delta I_{O(m)}/\Delta I_{O(c)}$	$-100\mu\text{A} < I_{O(c)} < 100\mu\text{A}$, $1.5\text{V} < V_i < 5.5\text{V}$, $3\text{V} < V_{O(m)} < 6\text{V}$	0.9	1.0	1.1	
		at CRT discharge, $I_{O(c)} = 1\text{mA}$, $1.5\text{V} < V_i < 5.5\text{V}$, $3\text{V} < V_{O(m)} < 5.4\text{V}$		1.0		
Maximum Peak Output Current (Pin7, Pin8 and Pin9)	$I_{O(c)(max)}$	$50\text{V} < V_{O(c)} < V_{DD} - 50\text{V}$		20		mA
Minimum Output Voltage (Pin7, Pin8 and Pin9)	$V_{O(c)(min)}$	$V = 7\text{V}$			10	V
Maximum Output Voltage (Pin7, Pin8 and Pin9)	$V_{O(c)(max)}$	$V = 1\text{V}$	$V_{DD}-15$			V
Small Signal Bandwidth (Pin7, Pin8 and Pin9)	B_S	$V_{O(c)} = 60\text{V(p-p)}$		5.5		MHz
Large Signal Bandwidth (Pin7, Pin8 and Pin9)	B_L	$V_{O(c)} = 100\text{V(p-p)}$		4.5		MHz
Cathode Output Propagation Time 50% input to 50% output (Pin7, Pin8 and Pin9)	t_{PCO}	$V_{O(c)} = 100\text{V(p-p)}$ square wave, $f < 1\text{MHz}$, $t_r = t_f = 40\text{ns}$ (Pin1, Pin2 and Pin3)		60		ns
Difference in Cathode Output Propagation Time 50% input to 50% output (Pin7 and Pin8, Pin7 and Pin9 and Pin8 and Pin9)	Δt_{PCO}	$V_{O(c)} = 100\text{V(p-p)}$ square wave, $f < 1\text{MHz}$, $t_r = t_f = 40\text{ns}$ (Pin1, Pin2 and Pin3)	-10	0	+10	ns
Cathode Output Rise Time 10% Output to 90% Output (Pin7, Pin8 and Pin9)	$t_{O(r)}$	$V_{O(c)} = 50$ to 150V square wave, $f < 1\text{MHz}$; $t_r = 40\text{ns}$ (Pin1, Pin2 and Pin3)	67	91	113	ns
Cathode Output Fall Time 90% output to 10% Output (Pin7, Pin8 and Pin9)	$t_{O(f)}$	$V_{O(c)} = 150$ to 50V square wave, $f < 1\text{MHz}$, $t_r = 40\text{ns}$ (Pin1, Pin2 and Pin3)	67	91	113	ns

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$, $V_{DD} = 200\text{V}$, $V_{o(c1)} = V_{o(c2)} = V_{o(c3)} = 1/2V_{DD}$, $C_L = 10\text{ pF}$ (C_L consists of parasitic and cathode capacitance), $R_{th(H-A)} = 18\text{K/W}$ unless otherwise specified.)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Setting Time 50% Input to 99% < output < 101% (Pin7, Pin8 and Pin9)	t_{st}	$V_{o(c)} = 100\text{V}$ (p-p) square wave, $f < 1\text{MHz}$; $t_r = t_f = 40\text{ns}$ (Pin1, Pin2 and Pin3)			350	ns
Slew Rate Between 50V to ($V_{DD} - 50\text{V}$) (Pin7, Pin8 and Pin9)	SR	$V_i = 4\text{V}$ (p-p) square wave, $f < 1\text{MHz}$; $t_r = t_f = 40\text{ns}$ (Pin1, Pin2 and Pin3)		900		V/ μs
Cathode Output Voltage Overshoot (Pin7, Pin8 and Pin9)	O_v	$V_{o(c)} = 100\text{V}$ (p-p) square wave, $f < 1\text{MHz}$; $t_r = t_f = 40\text{ns}$ (Pin1, Pin2 and Pin3)		2		%
Power Supply Rejection Ratio	PSRR	$f < 50\text{kHz}$, Note 2		55		dB
DC Crosstalk Between Channels	$\alpha_{ct(DC)}$			50		dB

Note 2. The ratio of the change in supply voltage to the change in input voltage when there is no change in output voltage.

