

Date-Issued: 7/5/2011 SDS Ref. No: RX1401-16 Date-Revised: 11/7/2017 Revision No: 002

ECG Electronics HD Cleaning Solvent RX1401-16

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Brand Name	RX1401-16
Product Description:	ECG Electronics HD Cleaning Solvent
Product Code	RX1401-16
Marketer Contact Information:	NTE Electronics, Inc.
	44 Farrand Street
	Bloomfield, NJ 07003
	973-748-5089
Emergency Phone:	CHEMTREC 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

OSHA/HCS Status	This material is considered hazardous by the OSHA Hazard
	Communication Standard (29 CFR 1910.1200)
Classification of the Substance or Mixture	SKIN CORROSION/IRRITTION – Category 2
	SERIOUS EYE DAMAGE/EYE IRRITATION – Category 2a
	GASES UNDER PRESSURE – Compressed gas
	Percentage of the mixture consisting of ingredient(s) of unknown
	toxicity: 2%

GHS Label Elements

Hazard Pictograms	
Single Word	Danger
Hazard Statements	Causes serious eye irritation.
	Causes skin irritation.
	Contains gas under pressure; may explode if heated.

Precautionary Statements

<u>I Tecuditonal y Bratements</u>	
Prevention	Wear protective gloves. Wear eye or face protection. Keep away
	from heat, hot surfaces, sparks, open flames, and other ignition
	sources. No smoking. Pressurized container: Do not pierce or burn,
	even after use. Do not spray on an open flame or other ignition
	source. Wash hands thoroughly after handling.
Response	IF ON SKIN: Wash with plenty of soap and water. Take off
	contaminated clothing. Wash contaminated clothing before reuse. If
	skin irritation occurs: Get medical attention. IF IN EYES: Rinse
	cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing. If eye irritation persists:
	Get medical attention.
Storage	Protect from sunlight. Do not expose to temperatures exceeding
	+50°C/+122°F. Store in a well-ventilated place.
Disposal	Not Applicable.
Hazards Not Otherwise Classified	None known

SECTION 3. COMPOSITION / INFORMATION OF INGREDIENTS	
Substance/Mixture	Mixture
Other Means of Identification	Fluxing agents Remover.

CAS Number/Other Identifiers

end number outer radiations	
CAS Number	Not applicable
Product Code	RX1401-16

Ingredient Name	%	CAS Number
Trans-Dichloroethylene	50 - 70	156-60-5
Ethyl Alcohol	1 - 5	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

Wash out mouth with water. Remove dentures if any. Remove Ingestion victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as collar, tie, belt, or waistband. Remove victim to fresh air and keep at rest in a position comfortable Inhalation for breathing. If not breathing, if breathing is irregular, or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt, or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Flush contaminated skin with plenty of water. Remove contaminated **Skin Contact** clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. Immediately flush eyes with plenty of water, occasionally lifting the **Eye Contact** upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

SECTION 4. FIRST-AID MEASURES Description of Necessary First Aid Measures

Most Important Symptoms/Effects, Acute and Delayed

Potential Acute Health Effects

Eye Contact	Causes serious eye irritation
Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin Contact	Causes skin irritation.
Ingestion	Irritating to mouth, throat, and stomach.

SECTION 4. FIRST-AID MEASURES (Cont'd)

Over-Exposure Sign/Symptoms

Over-Exposure Sign/Symptoms	
Eye Contact	Adverse symptoms may include the following:
	Pain or irritation
	Watering
	Redness
Inhalation	Adverse symptoms may include the following:
	Respiratory tract irritation
	Coughing
Skin Contact	Adverse symptoms may include the following:
	Irritation
	Redness
Ingestion	Adverse symptoms may include the following:
	Nausea or vomiting
	Diarrhea

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician	In case of inhalation of decomposition products in a fire, symptoms
	may be delayed. The exposed person may need to be kept under
	medical surveillance for 48 hours.
Specific Treatments	No specific treatment.
Protection of First-Aiders	No action shall be taken involving any personal risk or without
	suitable training. It may be dangerous to the person providing aid to
	give mouth-to-mouth resuscitation.

See Toxicological Information (Section 11)

SECTION 5. FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable Extinguishing Media:	None known.
Specific Hazards Arising from the Chemical:	Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from fire at high speed. Runoff to sewer may create fire or explosion hazard.
Hazardous Thermal Decomposition Products	Decomposition products may include the following materials: Carbon Dioxide Carbon Monoxide Halogenated Compounds Carbonyl Halides
Special Protective Actions for Firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special Protective Equipment or Firefighters	Firefighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6. ACCIDENTAL RELEASE MEASURES Personal Precautions, Protective Equipment and Emergency Procedures

Tersonal Trecautions, Trotective Equipment and	
For Non-Emergency Personnel	No action shall be taken involving any personal risk without suitable
	training. Evacuate surrounding areas. Keep unnecessary and
	unprotected personnel from entering. In the case of aerosols being
	ruptured, care should be taken due to the rapid escape of the
	pressurized contents and propellant. If a large number of containers
	are ruptured, treat as a bulk material spillage according to the
	instructions in the clean-up section. Do not touch or walk through
	spilled material. Shut off all ignition sources. No flares, smoking or
	flames in hazard area. Avoid breathing vapor or mist. Provide
	adequate ventilation. Wear appropriate respirator when ventilation is
	inadequate. Put on appropriate personal protective equipment.
For Emergency Responders	If specialized clothing is required to deal with the spillage, take note
	of any information in Section 8 on suitable and unsuitable materials.
	See also the information in "For Non-Emergency Personnel".
Environmental Precautions	Avoid dispersal of spilled material and runoff and contact with soil,
	waterways, drains, and sewers. Inform the relevant authorities if the
	product has caused environmental pollution (sewers, waterways,
	soil, or air).

Methods and Materials for Containment and Cleaning Up

Wethous and Waterials for Containment and Cleaning Op			
Small Spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large Spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements, or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite, or diatomaceous earth and place in container for disposal according to local regulations (See Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: See Section 1 for emergency contact information and Section 13 for waste disposal.		

SECTION 7. HANDLING AND STORAGE Precautions for Safe Handling

Trecautions for Sale Handling			
Protective Measures	Put on appropriate personal protective equipment (See Section 8).		
	Pressurize container: protect from sunlight and do not expose to		
	temperatures exceeding +50°C. Do not pierce or burn, even after		
	use. Do not ingest. Avoid contact with eyes, skin, and clothing.		
	Avoid breathing gas. Avoid breathing vapor or mist. Use only with		
	adequate ventilation. Wear appropriate respirator when ventilation is		
	inadequate. Store and use away from heat, sparks, open flame or any		
	other ignition source. Use explosion-proof electrical (ventilating,		
	lighting and material handling) equipment. Use only non-sparking		
	tools. Empty containers retain product residue and can be hazardous.		
Advice on General Occupational Hygiene	Eating, drinking, and smoking should be prohibited in areas where		
	this material is handled, stored, and processed. Workers should wash		
	hands and face before eating, drinking, and smoking. Remove		
	contaminated clothing and protective equipment before entering		
	eating areas. See also Section 8 for additional information on		
	hygiene measures.		

SECTION 7. HANDLING AND STORAGE (Cont'd)

Precautions for Safe Handling (Cont'd)

Conditions for Safe Storage, Including any	Store
Incompatibilities	sunli
	inco
	Flim

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool, and well ventilated area, away from incompatible materials (See Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

Ingredient Name	Exposure Limits	
Trans-Dichloroethylene	ACGIH TLV (United States, 4/2014).	
	TWA: 200ppm 8 hours	
	TWA: 793 mg/m ³ 8 hours	
Ethyl Alcohol	ACGIH TLV (United States, 4/2014).	
	STEL: 1000ppm 15 minutes	
	NIOSH REL (United States, 10/2013).	
	TWA: 1900mg/m ³ 10 hours	
	TWA: 1000ppm 10 hours	
	OSHA PEL (United States, 2/2013).	
	TWA: $1900 \text{mg/m}^3 8 \text{ hours}$	
	TWA: 1000ppm 8 hours	
	OSHA PEL (United States, 3/1989).	
	TWA: $1900 \text{mg/m}^3 8 \text{ hours}$	
	TWA: 1000ppm 8 hours	

Appropriate Engineering Controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor, or dust concentrations below any lower explosive limits. Use explosion- proof ventilation equipment.
Environmental Exposure Control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters, or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures	Wash hands, forearms, and face thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety		
	showers are close to the workstation location.		
Eye/Face Protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.		

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (Cont'd) <u>CONTROL PARAMETERS (Cont'd)</u> <u>Skin Protection</u>

Hand Protection	Chemical-resistant, impervious gloves, complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective
	properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the
	protection time of the gloves cannot be accurately estimated.t
Body Protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti- static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other Skin Protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection

<u>Respiratory resection</u>	
Respiratory Protection	Use a properly fitted, air-purifying or air-fed respirator complying
	with an approved standard if a risk assessment indicates this is
	necessary. Respirator selection must be based on known or
	anticipated exposure levels, the hazards of the product and the safe
	working limits of the selected respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Appearance		
Physical State	Liquid	
Color	Clear. Colorless	
Odor	Ethereal. (Slight)	
Odor Threshold Not Available.		
рН	Not Available.	
Melting Point	Not Available	
Boiling Point	+39°C (+102.2°F)	
Flash Point	Not Available	
Evaporation Rate	Not Available	
Flammability (Solid, Gas)	Not Available.	
Lower and Upper Explosive (Flammable) Limits Lower: 4.6%		
	Upper: 12.8%	
Vapor Pressure	19.3kPa (144.85mm Hg) [room temperature]	
Vapor Density	Not Available	
Relative Density	1.22	
Solubility	Not Available	
Partition Coefficient: n-octanol/water	Not Available	
Auto-Ignition Temperature	Not Available	
Decomposition Temperature	Not Available	
Viscosity	Not Available	

Aerosol Product	
Type of Aerosol	Spray
Heat of Combustion	0.84kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	No specific test data related to reactivity available for this product			
	or its ingredients.			
Chemical Stability	This product is stable.			
Possibility of Hazardous Reactions	Under normal conditions of storage and use, hazardous reactions			
	will not occur.			
Conditions to Avoid	Avoid all possible sources of ignition (spark or flame). Elevated			
	temperature.			
Incompatible Materials	Reactive or incompatible with the following materials:			
	Oxidizing materials alkalis			
Hazardous Decomposition Products	Under normal conditions of storage and use, hazardous			
	decomposition products should not be produced.			

SECTION 11. TOXICOLOGICAL INFORMATION INFORMATION ON TOXICOLOGICAL EFFECTS Acute Toxicity

Atur Toxity				
Product/Ingredient Name	Result	Species	Dose	Exposure
Trans-Dichloroethyene	LC Inhalation Gas	Rat	24100ppm	4 hours
	LD50 Dermal	Rabbit	> 5g/kg	-
	LD50 Oral	Rat	1235mg/kg	-
Ethyl Alcohol	LC50 Inhalation Vapor	Rat	124700mg/m ³	4 hours
	LD50 Oral	Rat	7g/kg	-

Irritation/Corrosion

Product/Ingredient Name	Result	Species	Score	Exposure	Observation
Trans-Dichloroethyene	Eyes – Moderate Irritant	Rabbit	-	10 milligrams 24 hours	-
	Skin – Moderate Irritant	Rabbit	-	500 milligrams 24 hours	-
Ethyl Alcohol	Eyes – Mild Irritant	Rabbit	-	500 milligrams	-
				0.0666666667 minutes	
	Eyes – Moderate Irritant	Rabbit	-	100 milligrams	-
	Eyes – Moderate Irritant	Rabbit	-	100 microliters	-
	Eyes – Severe Irritant	Rabbit	-	500 milligrams	-
	Skin – Mild Irritant	Rabbit	-	400 milligrams 24 hours	-
	Skin – Moderate Irritant	Rabbit	-	20 milligrams	-

 Sensitization

 Conclusion/Summary
 Not Available

Mutagenicity

Conclusion/Summary	Not Available

<u>Carcinogenicity</u>		
Conclusion/Summary	Not Available	

Classification

Product/Ingredient Name	OSHA	IARC	NTP
Ethyl Alcohol	-	1	-

Reproductive Toxicity

Conclusion/Summary	Not Available

Teratogenicity

Conclusion/Summary Not Available

Specific Target Organ Toxicity (Single Exposure)	
Conclusion/Summary	Not Available

SECTION 11. TOXICOLOGICAL INFORMATION (Cont'd) INFORMATION ON TOXICOLOGICAL EFFECTS (Cont') Specific Target Organ Toxicity (Repeated Exposure)

<u>Specific Target Organ Toxicity (Repeated Exposure)</u>	
Conclusion/Summary	Not Available

Aspiration Hazard

Conclusion/Summary	Not Available	

Information on the Likely Routes of Exposure	Not Available

Potential Acute Health Effects

Eye Contact	Causes serious eye irritation.
Inhalation	Exposure to decomposition products may cause a health
	hazard. Serious effects may be delayed following exposure
	exposure
Skin Contact	Causes skin irritation.
Ingestion	Irritation to mouth, throat, and stomach.

Symptom Related to the Physical, Chemical, and Toxicological Characteristics

Eye Contact	Adverse symptoms may include the following:
	Pain or irritation
	Watering
	Redness
Inhalation	Adverse symptoms may include the following:
	Respiratory Tract Irritation
	Coughing
Skin Contact	Adverse symptoms may include the following:
	Irritation
	Redness
Ingestion	Adverse symptoms may include the following:
	Nausea or Vomiting
	Diarrhea

Delayed and immediate Effects and also Chronic Effects from Short and Long Term Exposure

Short Term Exposure	
---------------------	--

Potential Immediate Effects	Not Available
Potential Delayed Effects	Not Available

Long Term Exposure

Potential Immediate Effects	Not Available
Potential Delayed Effects	Not Available

Potential Chronic Health Effects

Conclusion/Summary Not Available	
----------------------------------	--

General	No Known Significant Effects of Critical Hazards
Carcinogenicity	No Known Significant Effects of Critical Hazards
Mutagenicity	No Known Significant Effects of Critical Hazards
Teratogeniity	No Known Significant Effects of Critical Hazards
Developmental Effects	No Known Significant Effects of Critical Hazards
Fertility Effects	No Known Significant Effects of Critical Hazards

Numerical Measures of Toxicity Acute Toxicity Estimates

Acute Toxicity Estimates		
Route	ATE Value	
Oral	2058.3mg/kg	

SECTION 12. ECOLOGICAL INFORMATION Toxicity

Product/Ingredient Name	Result	Species	Exposure
Trans-Dichloroethyene	Acute LC50 220000 to 290000µg/l	Daphnia – Daphnia Magna	48 hours
	Fresh Water		
Ethyl Alcohol	Acute EC50 17.921mg/l Marine Water	Algae – Ulva Pertusa	96 hours
	Acute EC50 2000µg/l Fresh Water	Daphnia – Daphnia Magna	48 hours
	Acute LC50 25500µg/l Marine Water	Crustaceans – Artemia	48 hours
		Franciscana – Larvae	
	Acute LC50 42000µg/l Fresh Water	Fish – Oncorhynchus Mykiss	4 days
	Chronic NOEC 4.995mg/l Marine Water	Algae – Ulva Pertusa	96 hours
	Chronic NOEC 0.375µl/L Fresh Water	Fish – Gambusia Holbrooki -	12 weeks
		Larvae	

Persistence/Degradability

Conclusion/Summary	Not Available

Bioaccumulative Potential

Product/Ingredient Name	LogPow	BCF	Potential
Trans-Dichloroethyene	2.09	-	Low
Ethyl Alcohol	-0.35	-	Low

Mobility in Soil

Soil/Water Partition Coefficient (K _{OC})	Not Available
---	---------------

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods	The generation of waste should be avoided or minimized wherever possible. Disposal of			
	this product, solutions, and any other by-products should at all times comply with the			
	requirements of environmental protection and waste disposal legislation and any regional			
	local authority requirements. Disposal of surplus and non-recyclable products via a			
	licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer			
	unless fully compliant with the requirements of all authorities with jurisdiction. Waste			
	packaging should be recycled. Incineration or landfill should only be considered when			
	recycling is not feasible. This material and its container must be disposed of in a safe way.			
	Empty containers or liners may retain some product residues. Do not puncture or incinerate			
	container.			

United States - RCRA Toxic Hazardous Waste "U" List

Ingredient	CAS #	Status	Reference Number
1,2-Dichloroethylene; Ethene, 1,2-Dichloro-, €-	156-60-5	Listed	U079

SECTION 14. TRANSPORT INFORMATION

	DOT	TDG	Mexico			
	Classification	Classification	Classification	ADR/RID	IMDG	IATA
UN Number	-	-	-	UN1950	UN1950	ID8000
UN Proper	Consumer	Consumer	Consumer	(Trans-	AEROSOLS	Consumer
Shipping Name	Commodity ORM-D	Commodity ORM-D	Commodity ORM-D	dichloroethylene, ethanol)	IN LIMITED QUANTITIES OF CLASS 2	Commodity ID8000
Transport Hazard Class(es)	ORM-D	ORM-D	ORM-D	2	2.1	9
Packing Group	-	-	-	-	-	-
Environmental Hazards	No	No	No	No	No	No

SECTION 14. TRANSPORT INFORMATION (Cont'd)

	DOT	TDG	Mexico			
	Classification	Classification	Classification	ADR/RID	IMDG	IATA
Additional	Reportable	-	-	Tunnel code	-	-
Information	<u>quantity</u>			(D)		
	1666.lbs. /					
	756.67 kg					
	[163.84 gal /					
	620.22 L]					
	Package sizes					
	shipped in					
	quantities less					
	than the product					
	reportable					
	quantity are no					
	subject to the					
	RQ (reportable					
	quantity)					
	transportation					
	requirements.					

Special Precautions for User	Transport within user's premises: always transport in	
	closed containers that are upright and secure. Ensure that	
	persons transporting the product know what to do in the	
	event of an accident or spillage.	

Transport in Bulk According to Annex II of MARPOL	Not Available
73/78 and the IBC Code	

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA 5(a)2 – Final Significant New Use Rules	Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-
TSCA 8(a) – CDR Exempt/Partial Exemption	Not Determined
TSCA 12(b) One-Time Export	Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-
	All components are listed or exempted.
Clean Water Act (CWA) 307	Trans-Dichloroethylene

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

Classification Not Listed		
	Classification	Not Listed

Clean Air Act Section 602 Class I Substances

	Classification	Not Listed
--	----------------	------------

Clean Air Act Section 602 Class II Substances	
Classification	Not Listed

DEA List I Chemicals (Precursor Chemicals)

Classification	Not Listed

DEA List II Chemicals (Essential Chemicals)

Classification	Not Listed

SARA 302/304

Composition/Information on Ingredients	No Products Were Found

<u>SARA 304 RQ</u>

Classification

SECTION 15. REGULATORY INFORMATION (Cont'd) <u>SARA 311/312</u> Classification

Fire Hazard. Immediate (acute) health hazard.

Composition/Information on Ingredients

					Immediate	Delayed
			Sudden		(Acute)	(Chronic)
			Release of		Health	Health
Name	%	Fire Hazard	Pressure	Reactive	Hazard	Hazard
Tuona Diahlana athrean a	50 50	* 7	27		3.7	NT
Trans-Dichloroethyene	50 - 70	Yes	No	No	Yes	No

State Regulations

Massachusetts	The Following Components are Listed: DICHLOROETHYLENE-TRANS; ETHYL	
	ALCOHOL; CARBON DIOXIDE	
New York	The Following Components are Listed: Ethene, trans-1,2-dichloro-; Dichloroethylene	
New Jersey	The Following Components are Listed: ETHYL ALCOHOL; ALCOHOL; CARBON	
	DIOXIDE; CARBONIC GAS	
Pennsylvania	The Following Components are Listed: ETHENE, 1,2-DICHLORO-, (E)-;	
	DENATURED ALCOHOL; CARBON DIOXIDE	

International Regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals		
Classification	Not Listed	

Not Listed

Montreal Protocol (Annexes A, B, C, E)

Classification

Stockholm Convention on Persistent Organic Pollutants

Classification

Not Listed

Rotterdam Convention on Prior Inform Consent (PIC)

Classification	Not Listed

UNECE Aarhus Protocol on POPs and Heavy Metals Classification Not Listed

International Lists

National Inventory	
Australia	All Components are Listed or Exempted.
Canada	All Components are Listed or Exempted.
China	All Components are Listed or Exempted.
Europe	Not Determined.
Japan	All Components are Listed or Exempted.
Malaysia	Not Determined.
New Zealand	All Components are Listed or Exempted.
Philippines	All Components are Listed or Exempted.
Republic of Korea	All Components are Listed or Exempted.
Taiwan	Not Determined.

SECTION 16. OTHER INFORMATION

Hazardous Material Information System (U.S.A.)

Health	2
Flammability	2
Physical Hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the national Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 system to classify chemicals does so at their own risk.

Further Information

This information above is believed to be accurate and represents the best information currently available to us. However, neither NTE nor any of its subsidiaries make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.