

Material Safety Data Sheet

acc. to ISO/DIS 11014

Kester

Printing date 05/23/2003

Reviewed on 04/03/2003

1 Identification of substance

Product details

Trade name: 2331ZX

Application of the substance / the preparation: Soldering flux

Manufacturer/Supplier:

Northrop Grumman Kester
515 E. Touhy Ave.
Des Plaines, IL 60018

Tel.(847) 297-1600
Fax.(847) 390-9338

Information department:

MSDS Coordinator

Tel. (847) 699-5755

Emergency information:

CHEMTREC 24-Hour Emergency Telephone Number:

(800)424-9300

CHEMTREC 24-Hour Emergency Telephone Number (Outside of the U.S. and Canada):

(703)527-3887

2 Composition/Data on components

Chemical characterization

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-63-0	propan-2-ol	50-100%
56-81-5	glycerol	10-25%
111-42-2	2,2'-iminodiethanol	2.5-10%
506-59-2	dimethylammonium chloride	2.5-10%
50-21-5	lactic acid	2.5-10%
79-14-1	glycollic acid	≤ 2.5%

Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

WHMIS Hazard Symbols



Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Has a narcotizing effect.

Highly flammable.

Irritating to eyes.

Vapours may cause drowsiness and dizziness.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 2)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Kester

Printing date 05/23/2003

Reviewed on 04/03/2003

Trade name: 2331ZX

(Contd. of page 1)

HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Seek immediate medical advice.

5 Fire fighting measures

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards caused by the material, its products of combustion or resulting gases:

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Aliphatic aldehydes

Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

Person-related safety precautions: Ensure adequate ventilation

Measures for environmental protection: Do not allow product to reach sewage system or any water course.

Measures for cleaning/collecting:

Absorb with clay, dry sand, or other inert material. Do not use combustible materials such as sawdust. Place in a chemical waste container.

7 Handling and storage

Handling:

Information for safe handling: Store in cool, dry place in tightly closed receptacles.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

(Contd. on page 3)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Kester

Printing date 05/23/2003

Reviewed on 04/03/2003

Trade name: 2331ZX

(Contd. of page 2)

Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

Additional information about design of technical systems: No further data; see item 7.

Components with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

PEL	980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: (1230) mg/m ³ , (500) ppm Long-term value: (983) mg/m ³ , (400) ppm NIC-200; 491; 400; 984; A 4

56-81-5 glycerol

PEL	15*; 5** mg/m ³ *Total dust **Respirable fraction
-----	---

111-42-2 2,2'-iminodiethanol

REL	15 mg/m ³ , 3 ppm
TLV	2 mg/m ³ , 0.46 ppm Skin

Additional information:

- PEL = Permissible Exposure Limit (OSHA)
- REL = Recommended Exposure Limit (NIOSH)
- TLV = Threshold Limit Value (ACGIH)
- OSHA = Occupational Safety and Health Administration
- ACGIH = American Conference of Governmental Industrial Hygienists
- NIOSH = National Institute for Occupational Safety and Health

Personal protective equipment:

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

Breathing equipment:

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

Protection of hands:



Protective gloves

Material of gloves:
Nitrile rubber, NBR
Natural rubber, NR

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Kester

Printing date 05/23/2003

Reviewed on 04/03/2003

Trade name: 2331ZX

(Contd. of page 3)

Eye protection:



Tightly sealed goggles

Safety glasses

9 Physical and chemical properties

General Information

Form: Liquid
Color: Amber colored
Odor: Alcohol-like

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 82°C (180°F)

Flash point: 18°C (64°F)

Ignition temperature: 370.0°C (698°F)

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Explosion limits:

Lower: 0.9 Vol %
Upper: 12.0 Vol %

Vapor pressure at 20°C (68°F): 33 hPa (25 mm Hg)

Density at 20°C (68°F): 0.899 g/cm³

Solubility in / Miscibility with

Water: Soluble.

pH-value at 20°C (68°F): 6.7

10 Stability and reactivity

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Materials to be avoided: Strong acids, strong oxidizers.

Dangerous reactions No dangerous reactions known.

Dangerous products of decomposition:

When heated to soldering temperatures, solvents will be evaporated and organic material may release aliphatic aldehydes and acids.

USA

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Kester

Printing date 05/23/2003

Reviewed on 04/03/2003

Trade name: 2331ZX

(Contd. of page 4)

11 Toxicological information

Acute toxicity:

LD/LC50 values that are relevant for classification:

67-63-0 propan-2-ol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

111-42-2 2,2'-iminodiethanol

Oral	LD50	1600 mg/kg (rat)
Dermal	LD50	12200 mg/kg (rabbit)

Primary irritant effect:

on the skin: Possible local irritation by contact with flux or fumes.

on the eye: Smoke during soldering can cause eye irritation.

through inhalation:

Fumes during use may irritate mucous membranes and respiratory system. High concentrations can cause headache, dizziness, narcosis, and nausea.

through ingestion: May cause gastrointestinal irritation.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

12 Ecological information

General notes: Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

Product:

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

DOT regulations:

Hazard class: 3
 Identification number: UN1219
 Packing group: I
 Proper shipping name (technical name): ISOPROPANOL, mixture
 Label: 3

Land transport ADR/RID (cross-border):

ADR/RID class: 3 Flammable liquids

(Contd. on page 6)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Kester

Printing date 05/23/2003

Reviewed on 04/03/2003

Trade name: 2331ZX

(Contd. of page 5)

Danger code (Kemler): 33
UN-Number: 1219
Packaging group: I
Description of goods: ISOPROPANOL, mixture

Maritime transport IMDG:
IMDG Class: 3
UN Number: 1219
Label: 3
Packaging group: I
EMS Number: F-E,S-E
Marine pollutant: No
Propper shipping name: ISOPROPANOL, mixture

Air transport ICAO-TI and IATA-DGR:
ICAO/IATA Class: 3
UN/ID Number: 1219
Label: 3
Packaging group: I
Propper shipping name: ISOPROPANOL, mixture

15 Regulations

USA The following information relates to product regulation specific to the USA.

SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

67-63-0 | *propan-2-ol*

111-42-2 | *2,2'-iminodiethanol*

TSCA (Toxic Substances Control Act):

All ingredients are listed.

California Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

Carcinogenicity categories

EPA (Environmental Protection Agency)

None of the ingredients is listed.

IARC (International Agency for Research on Cancer)

67-63-0 | *propan-2-ol* | 3

NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Kester

Printing date 05/23/2003

Reviewed on 04/03/2003

Trade name: 2331ZX

(Contd. of page 6)

TLV (Threshold Limit Value established by ACGIH)
None of the ingredients is listed.
NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients is listed.
OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

CANADA: The following information relates to product regulation specific to Canada.

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

WHMIS Classification:

B2
D2B

Components on Ingredient List for WHMIS:

propan-2-ol
2,2'-iminodiethanol
lactic acid
glycollic acid

EUROPEAN UNION

The following information relates to product regulation specific to the directives of the European Union.

Risk phrases:

Highly flammable.
Irritating to eyes.
Vapours may cause drowsiness and dizziness.

Safety phrases:

Keep out of the reach of children.
Keep container tightly closed in a cool place.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
If swallowed, seek medical advice immediately and show this container or label.

16 Other information

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Northrop Grumman Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Department issuing MSDS: Product Safety
Contact: Heather Holich, MSDS Coordinator

Tel. (847)699-5755