









# Selector Guide

Buzzers		Impulse/Latching Relays		PC Mount
Series	RB	R50	RLY76 & 77	R21
				
Features	<ul style="list-style-type: none"> <li>• AC Operated</li> <li>• Lightweight</li> <li>• Audible Signal Source</li> </ul>	<ul style="list-style-type: none"> <li>• Dust Cover</li> <li>• Magnetic Latching</li> <li>• .187" Quick Connect Terminals</li> </ul>	<ul style="list-style-type: none"> <li>• Open Frame</li> <li>• Bistable</li> <li>• Pulse Operation</li> <li>• .250" Quick Connect Terminals</li> </ul>	<ul style="list-style-type: none"> <li>• Subminiature Size</li> <li>• Epoxy Sealed</li> <li>• Class B</li> </ul>
Contact Arrangement		SPDT, DPDT	DPDT	SPDT
Contact Ratings		10A @ 28VDC/120VAC	15A @ 28VDC/120VAC	1A, 2A @ 30VDC/125VAC
Coil Voltage	12, 24, 120, 240VAC	120VAC 12, 24VDC	24, 120VAC 12, 24VDC	6, 12, 24VDC
Nominal Coil Power AC Types DC Types	3VA –	1.7VA 1.2W	9VA 6.5W	– 200, 360mW
Options ( ) Suffix		Dual Coil (C)		
Page	115	55	84	34

PC Mount (Cont'd)				
Series	R22	R23	R24	R25
				
Features	<ul style="list-style-type: none"> <li>• Dust Cover</li> <li>• Low Coil Power</li> <li>• Small Size</li> <li>• TV-5 Type</li> </ul>	<ul style="list-style-type: none"> <li>• Epoxy Sealed</li> <li>• Class B Insulation</li> </ul>	<ul style="list-style-type: none"> <li>• Epoxy Sealed for Wave Soldering and Immersion Cleaning</li> <li>• Upright or Flat-Pack</li> </ul>	<ul style="list-style-type: none"> <li>• Epoxy Sealed</li> <li>• Immersion Proof</li> <li>• Upright Package Type</li> </ul>
Contact Arrangement	SPST-NO, SPDT	SPDT	SPDT	SPST-NO, SPDT, DPDT
Contact Ratings	16A @ 30VDC/120VAC	20A @ 24VDC/277VAC	8A, 10A @ 28VDC/120VAC	10A, 16A @ 28VDC/120VAC
Coil Voltage	3, 5/6, 12, 24, 48VDC	6, 12, 24VDC	5/6, 6, 12, 24VDC	24, 120VAC 5/6, 12, 24, 48VDC
Nominal Coil Power AC Types DC Types	– 540, 720mW	– 270mW	– 600mW	– 500mW
Options ( ) Suffix			Upright Version (V) Flat-Pack Version (FP)	
Page	35	36	34	37