









Selector Guide

PC Mount (Cont'd)

Series	R73	R74	RLY34	RLY39
				
Features	<ul style="list-style-type: none"> Epoxy Sealed for Wave Soldering and Immersion Cleaning Small Size 	<ul style="list-style-type: none"> Standard .100" PC Board Spacing Low Power Consumption 	<ul style="list-style-type: none"> Sealed Construction Rated for D 150 Pilot Duty .100" Pin Spacing 	<ul style="list-style-type: none"> Epoxy Sealed Immersion Proof Low Profile
Contact Arrangement	SPST-NO, SPDT	DPDT	SPST-NO	SPDT, DPDT
Contact Ratings	10A @ 28VDC/120VDC	1A @ 30VDC	5A @ 30VDC/250VDC	2A @ 28VDC 1A @ 120VAC
Coil Voltage	3, 6, 12, 24, 48VDC	3, 5, 6, 12, 24VDC	5, 12, 24VDC	5-6, 12, 24VDC
Nominal Coil Power AC Types DC Types	— 450, 610mW	— 140, 200mW	— 200mW	— 600-860mW
Options () Suffix		Surface Mount (SM)		
Page	78	79	81	82

Reed Relays

Series	R42	R44	R56	R57
				
Features	<ul style="list-style-type: none"> .200" SIP Terminal Spacing TTL Compatible Internal Clamping Diode 	<ul style="list-style-type: none"> Standard .100" PC Board Spacing TTL Compatible 	<ul style="list-style-type: none"> Standard .100" DIP Terminal Spacing TTL Compatible 	<ul style="list-style-type: none"> Standard .100" DIP Terminal Spacing TTL Compatible
Contact Arrangement	SPST-NO	SPST-NO, DPST-NO	SPST-NO, SPDT, DPST-NO	SPST-NO, SPST-NC, SPDT
Contact Ratings	500mA @ 28VDC	5A Switching 2A Carry @ 200VDC	500mA @ 28VDC	250mA, 500mA @ 28VDC
Coil Voltage	5/6, 12, 24VDC	5/6, 12, 24VDC	5, 6, 12, 24VDC	5/6, 12, 24VDC
Nominal Coil Power AC Types DC Types	50, 77, 180mW	360, 510mW		
Options () Suffix	330μs Operate Time	500μs Operate Time	Diode Protection (D)	Diode Protection (D)
Page	48	49	62-63	62-63