



Recommended Cable Stripping Dim's

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 4. TEFLON

Crimped Ferrule
Hex Crimp Size .178 (4.5)
Crimped Contact Pin
Hex Crimp Size .043 (1.1)

RoHS Compliant

9	Ferrule	Note 1	Note 2	1	
8	Contact Pin	Note 1	Note 3	1	
7	Washer	Note 1	Note 2	1	
6	Spring	SK5	Note 2	1	
5	Retaining Ring	Note 1	Note 2	1	
4	Gasket	Rubber	Red	1	
3	Insulator	Note 4	Natural	1	
2	Body	Note 1	Note 2	1	
1	Shell	Note 1	Note 2	1	
No.	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches			
Unless Otherwise Specified Tolerances			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

Part No.		Date	
Approved		3-8-2018	
Checked		3-8-2018	
Drawn		3-8-2018	

NTE Electronics	
Title	BNC Crimp Plug (For AT&T 735A Cable)
Drawing No.	06-B003
File No.	