



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Phosphor Bronze
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. DELRIN

RoHS Compliant

1. Max. Panel Thickness = .217 (5.5)

Dimensions are in Inches					Part No.		<h1>NTE Electronics</h1>	
Unless Otherwise Specified					Approved	Date		Title BNC Jack to Jack Bulkhead Isolated Adapter
Tolerances					Checked	Date		
0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4					Drawn	Date		Drawing No. 06-B012
					Date 8-27-2015		File No.	

No	Description	Material	Finish	Q'ty	Drawing No.	Scale	3/1	Issue	A
7	Hex-Nut	Note 1	Note 2	1					
6	Lock Washer	Note 1	Note 2	1					
5	Lock Ring	Iron	Note 2	1					
4	Contact Pin	Note 3	Note 4	1					
3	Insulator	Note 5	Natural	2					
2	Insulator	Note 5	White	1					
1	Body	Note 1	Note 2	1					