



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>

## NTE1032

### Linear Integrated Circuit, OTL Audio Power Amp, 1W

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Supply Voltage, $V_{CC}$ .....	9V
Output Current, $I_{O(\text{peak})}$ .....	1A
Power Dissipation (Note 1), $P_T$ .....	1.2W
Operating Temperature Range (Note 2), $T_{opr}$ .....	$-30^\circ$ to $+70^\circ\text{C}$
Storage Temperature Range, $T_{stg}$ .....	$-55^\circ$ to $+125^\circ\text{C}$

Note 1. Value at designated heat sink

Note 2. Value when attached to the heat sink plate ( $\theta_1 = 34^\circ\text{C}$ ) at  $P_T = 1.0\text{W}$

**Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$ ,  $V_{CC} = 6\text{V}$ ,  $R_L = 4\Omega$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Quiescent Current	$I_Q$		-	10	18	mA
Output Gain-Open Loop	$G_{V(OL)}$		-	90	-	dB
Closed Loop Gain	$G_V$		-	50	-	dB
Total Harmonic Distortion	THD	$P_{out} = 50\text{mW}$	-	0.3	1.0	%
Power Output	$P_{out}$	THD = 10%	0.8	1.0	-	W
Signal-to-Noise Ratio	S/N	$R_g = 0$ , $P_{out} = 50\text{mW}$ , with 20kHz L.P.F.	-	66	-	dB
Input Resistance	$R_{in}$		13	20	-	k $\Omega$

### Pin Connection Diagram

