



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE3183 & NTE3184 Discrete Blue LED Indicators 3mm (T-1)

Description:

The NTE3183 and NTE3184 are blue source color light emitting diodes made with GaN on SiC. It is recommended that a wrist strap or anti-electrostatic glove be used when handling these devices as static electricity and surge will damage these devices. All devices, equipment, and machinery must be electrically grounded.

Features:

- Low Power Consumption
- Solid State Blue Light Source
 - NTE3183 (Blue Diffused)
 - NTE3184 (Clear Blue)
- Suitable for use in Full Color LED Displays and Indicators in Diagnostic/Analytical Equipment

Absolute Maximum Ratings: (T_A = +25°C unless otherwise specified)

Reverse Voltage, V_R 5V
 DC Forward Current, I_F 30mA
 Peak Forward Current (Note 1), I_{FP} 200mA
 Power Dissipation, P_D 100mW
 Operating Temperature Range, T_{opr} -20° to +85°C
 Storage Temperature Range, T_{stg} -30° to +100°C
 Lead Temperature (During Soldering, .157 (4mm) below package base, 5sec max), T_L ... +260°C

Note 1. Pulse Width ≤ 100µs, Duty Cycle ≤ 1%.

Electro-Optical Characteristics: (T_A = +25°C unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	V _F	I _F = 20mA	3.0	-	3.4	V
Luminous Intensity	I _v	I _F = 20mA	50	-	100	mcd
NTE3183			100	-	200	mcd
Viewing Angle	2θ ^{1/2}		-	60	-	deg.
NTE3183			-	20	-	deg.
Peak Emission Wave Length	λ _{PEAK}		425	430	435	nm

