



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE53022 thru NTE53028 Bridge Rectifier, Single Phase, Glass Passivated, 35A

Features:

- Low Reverse Leakage Current
- Low Power Loss, High Efficiency
- Heatsink Integrated Epoxy Case for Maximum Heat Dissipation
- Low Thermal Resistance
- High Surge Current Capability
- Mounting: Through Hole with #10 Screw

Maximum Ratings and Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified.
 Single Phase, Half Wave, 60Hz, Resistive or Inductive Load, Note 1)

Maximum Recurrent Peak Reverse Voltage, V_{RRM}	
NTE53022	200V
NTE53026	600V
NTE53028	1000V
Working Peak Reverse Voltage, V_{RWM}	
NTE53022	200V
NTE53026	600V
NTE53028	1000V
Maximum RMS Bridge Input Voltage, V_{RMS}	
NTE53022	140V
NTE53026	420V
NTE53028	700V
Maximum DC Blocking Voltage, V_{DC}	
NTE53022	200V
NTE53026	600V
NTE53028	1000V
Maximum Average Forward Rectified Output Current ($T_C = +55^\circ\text{C}$), $I_{O(AV)}$	
	35A
Peak Forward Surge Current (8.3ms single half wave superimposed on rated load), I_{FSM}	
	400A
Maximum Forward Voltage Drop (Per element at 17.5A), V_F	
	1.1V
Maximum Reverse Current at Rated DC Blocking Voltage Per Element, I_R	
$T_A = +25^\circ\text{C}$	10 μA
$T_A = +125^\circ\text{C}$	500 μA
I^2t Rating for Fusing ($t < 8.3\text{ms}$), I^2t	
	660A ² s
Typical Junction Capacitance (Note 2), C_j	
	300pF
Typical Thermal Resistance, Junction-to-Case (Per element, Note 3), R_{thJC}	
	1.4 $^\circ\text{C}/\text{W}$
RMS Isolation Voltage from Case to Leads, V_{ISO}	
	2500V
Operating Temperature Range, T_J	
	-65 $^\circ$ to +150 $^\circ\text{C}$
Storage Temperature Range, T_{stg}	
	-65 $^\circ$ to +150 $^\circ\text{C}$

Note 1. For capacitive load, derate current by 20%.

Note 2. Measured at 1.0MHz and applied reverse voltage of 4.0VDC.

Note 3. Thermal resistance, junction-to-case, mounted on a 241 x 89 x 117mm Al heatsink.



