Fully Insulated Heavy Duty Clamp, 500 Amp

Features

- · High Impact, Glass-Filled Nylon Jaws
- Braided Copper Shunt
- Replaceable Copper Contact Pads
- Nut & Bolt or Crimp/Solder Lug Connection
- Overall Length: 6.500" (165.1mm)
- Jaw Opening: 1.700" (43.2mm)

NTE Type No.	Description
72-112-0	Fully Insulated Heavy Duty Clamp, Black
72-112-2	Fully Insulated Heavy Duty Clamp, Red



72-135 Series PVC Insulators

Features

- Fits 72–133 & 72–134
- 2 Required per Clip
- Flexible PVC Composition
- Overall Length: 4.500" (114.3mm)

NTE Type No.	Description
72-135-0	PVC Insulator for 72-133 & 72-134, Black
72-135-2	PVC Insulator for 72–133 & 72–134, Red



72-142 Series PVC Insulators

Features

- Fits 72-139, 72-140 & 72-141
- 2 Required per Clip
- Flexible PVC Composition
- Overall Length: 1.600" (40.64mm)

NTE Type No.	Description
72–142–0	PVC Insulator for 72–139, 72–140 & 72–141, Black
72–142–2	PVC Insulator for 72–139, 72–140 & 72–141, Red

